

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of GRM32ER71A226KE20# from the official website of Murata Manufacturing Co., Ltd.

GRM32ER71A226KE20#

"#" indicates a package specification code.



< List of part numbers with package codes > GRM32ER71A226KE20L GRM32ER71A226KE20K

Applications

| Unsuitable | Please be sure to read and comply with | |
|--------------------------|---|--|
| Applications | these "Precautions for use." | |
| Specific Applications | Consumer equipment,Industrial Equipment,Mobile Electronics,Medical equipment [GHTF A/B/C] except for implant equipment,Automotive infotainment/comfort equipment | |
| | Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product. | |



PackagingSpecificationsStandard
Packing
QuantityL180Embossed Tape1000K330Embossed Tape4000

| Mass (typ.) | | |
|-------------|---------|--|
| 1 piece | 110.0mg | |

Appearance & Shape





1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GRM32ER71A226KE20#

Note: This datasheet may be out of date. Please download the latest datasheet of GRM32ER71A226KE20# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=GRM32ER71A226KE20%23

"#" indicates a package specification code.



Specifications

| Length | 3.2±0.3mm |
|--|--------------|
| Width | 2.5±0.2mm |
| Thickness | 2.5±0.2mm |
| Capacitance | 22µF ±10% |
| Distance between external terminals g | 1.0mm min. |
| External terminal size e | 0.3mm min. |
| Operating Temperature Range | -55℃ to 125℃ |
| Rated Voltage | 10Vdc |
| Size code in inch(mm) | 1210 (3225M) |
| Capacitance change rate | ±15.0% |
| Temperature characteristics (complied standard) | X7R(EIA) |
| Temperature range of temperature characteristics | -55℃ to 125℃ |

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

