

PCJ-124D3M,303 ! PENDING OBSOLESCENCE



OEG | OEG Slimline PCB Relay PCN

TE Internal #: 1721531-3

TE Internal Description: PCJ-124D3M,303

Slim PCB Relay, PCN 3A/5A 3VDC

[View on TE.com >](#)

Relays, Contactors & Switches > Relays > Power Relays > Slim PCB Relay, PCN 3A/5A 3VDC



Power Relay Type: **Standard**

Coil Magnetic System: **Monostable, DC**

Coil Power Rating DC: **200 mW**

Coil Resistance: **2880 Ω**

Coil Special Features: **UL Coil Insulation Class A**

[All Slim PCB Relay, PCN 3A/5A 3VDC \(0\)](#)

Features

Product Type Features

| | |
|------------------|----------|
| Power Relay Type | Standard |
|------------------|----------|

Electrical Characteristics

| | |
|--|-----------------|
| Insulation Initial Dielectric Between Coil & Contact Class | 3500 – 4000 V |
| Insulation Initial Dielectric Between Open Contacts | 750 Vrms |
| Contact Limiting Making Current | 5 A |
| Contact Limiting Short-Time Current | 5 A |
| Contact Limiting Continuous Current | 5 A |
| Insulation Creepage Class | 5.5 – 8 mm |
| Coil Power Rating Class | 150 – 200 mW |
| Insulation Initial Dielectric Between Contacts & Coil | 4000 Vrms |
| Insulation Initial Resistance | 1000 M Ω |
| Insulation Creepage Between Contact & Coil | 8 mm [.315 in] |
| Contact Limiting Breaking Current | 5 A |

| | |
|---------------------------------|----------------------------|
| Coil Magnetic System | Monostable, DC |
| Coil Power Rating DC | 200 mW |
| Coil Resistance | 2880 Ω |
| Coil Special Features | UL Coil Insulation Class A |
| Coil Voltage Rating | 24 VDC |
| Contact Switching Load (Min) | 100mA @ 5V |
| Contact Switching Voltage (Max) | 30 VDC |
| Contact Voltage Rating | 250 VAC |

Body Features

| | |
|-----------------------------|---|
| Insulation Special Features | 7000V Initial Surge Withstand Voltage between Contacts & Coil |
| Product Weight | 4 g[.141 oz] |

Contact Features

| | |
|------------------------------|---------------|
| Contact Arrangement | 1 Form A (NO) |
| Contact Current Class | 2 – 5 A, 16 A |
| Contact Current Rating (Max) | 5 A |
| Contact Material | AgNi |
| Contact Number of Poles | 1 |
| Relay Terminal Type | PCB-THT |

Mechanical Attachment

| | |
|---------------------|-----------------------|
| Relay Mounting Type | Printed Circuit Board |
|---------------------|-----------------------|

Dimensions

| | |
|---|-------------------|
| Length Class (Mechanical) | 20 – 25 mm |
| Insulation Clearance Class | 5 – 8 mm |
| Height Class (Mechanical) | 14 – 15 mm |
| Insulation Clearance Between Contact & Coil | 7.5 mm[.295 in] |
| Width Class (Mechanical) | 6 – 8 mm |
| Product Width | 7 mm[.276 in] |
| Product Length | 20.39 mm[.803 in] |
| Product Height | 15.01 mm[.591 in] |

Usage Conditions

| | |
|---|---------------|
| Environmental Ambient Temperature Class | 70 – 85 °C |
| Environmental Ambient Temperature (Max) | 85 °C[185 °F] |

Packaging Features

| | |
|------------------|------|
| Packaging Method | Tray |
|------------------|------|

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

| | |
|---|---|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Wave solder capable to 265°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Also in the Series | [OEG Slimline PCB Relay PCN](#)



Power Relays(21)

Customers Also Bought



TE Part #1-1393212-0
T92S7D12-24



TE Part #9-1419128-8
OJ-SH-112LMH,000



TE Part #1871303-1
DYNAMIC D1000 REC CONT M PRE
TIN REEL



TE Part #350434-1
15P UMNL PIN HDR ASSY NATL



TE Part #350826-1
04P UMNL HDR ASSY PC 94VO



TE Part #350825-1
03P UMNL HDR ASSY PC 94VO



TE Part #5-2232265-3
PTL 1X3 PLUG HSG GLW WIRE KEY A
DGR



TE Part #1721531-5
PCJ-124D3MH,303



TE Part #3-794631-4
04P MICRO MNL ASSY,VRT,HDR LF

Documents

Product Drawings

[PCJ-124D3M,303](#)

English

CAD Files

[3D PDF](#)

[3D](#)

[Customer View Model](#)

[ENG_CVM_CVM_1721531-3_G.2d_dxf.zip](#)



English

Customer View Model

[ENG_CVM_CVM_1721531-3_G.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1721531-3_G.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[PCJ Series Relay Data Sheet English](#)

English

Product Specifications

[Definitions General Purpose Relays](#)

English