




Pushing Performance
Since 1945

InduCom 15p T&S-entry hexscrew M3



Part number	61 03 001 1016 160
Specification	InduCom 15p T&S-entry hexscrew M3
HARTING eCatalogue	https://b2b.harting.com/61030011016160

Identification

Category	Hoods/Housings
Series of hoods/housings	D-Sub InduCom
Type of hood/housing	Shell housing
Description of hood/housing	With internal earth

Version

Size	D-Sub 2
Cable entry	1x
Strain relief	An additional InduCom cable clamp or a crimp flange - ferrule combination is available dependant on the use of the cable.
Locking type	Hexagonal screw with captive washer Thread M3
ground connection	With internal grounding block
2 parts	Yes
Separable	Yes

Technical characteristics

Tightening torque	0.4 Nm ground connection
	0.4 Nm cover screw
	0.4 Nm Locking screw
Ambient temperature	-55 ... +125 °C
Degree of protection acc. to IEC 60529	IP30

Material properties

Material (hood/housing)	Zinc die-cast
Material (screw)	Steel, nickel plated



Pushing Performance
Since 1945

Material properties

Length	36.4 mm
Width	39.5 mm
Height	14.8 mm

Commercial data

Packaging size	1
Net weight	44 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140222540
eCl@ss	27440213 D-Sub hood