



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 10/27/16'		

NOTES:

- ELECTRICAL CHARACTERISTICS:
 - CONTACT RESISTANCE: 30mΩ Max.
 - DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC(rms) FOR 1 MINUTE.
 - INSULATION RESISTANCE: 1000MΩ Min.
 - VOLTAGE RATING:125V.
 - CURRENT RATING:1.5A.
 - VOLTAGE(LED):2.4V MAX.
- ENVIRONMENT CHARACTERISTICS:
 - TEMPERATURE: -0°C~+70°C.
- MATERIALS:
 - HOUSING:PA66 BLACK UL94 V-0
 - INSERT:PBT BLACK YELLOW UL94 V-0
 - CONTACT:COPPER ALLOY
 - CONTACT PLATING: SELECTIVE GOLD,6u" MIN IN CONTACT AREA
- PRODUCT NUMBER CODE:
DS1134-09-X X X X X

- Housing Materials
N: Nylon
- Contact Plating
S: Seclctive 6u" Gold
- Housing Color
B: Black
- No.Of Contacts
8: 8p8c
- Connector Type
S: Socket

PCB LAYOUT
THICKNESS=1.6mm

Pi n	Yellow	Green
P9	+	+
P10	-	-

GENERAL TOLERANCE	ANGLE TOLERANCE	PROJECTION	TITLE
X. ±0.60	X. ±5°		RJ45 ICM(10/100 Base-T 1 Port)
.X ±0.38	.X ±3°	UNITS mm	
.XX ±0.25	.XX ±2°	SHEET SIZE A4	SERIES DS1134-09 SERIES
DRAWING TYPE: CUSTOMER		晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD	
SCALE 1:1	SHEET 1 OF 1		
DRAWING NO. C-DS1134-09-XXXXX-A			