

REV	SYM	Revision Record	Appr.	Date
V0	KLS02006	New Version Release	Jenny	2023-11-22

Material
Housing: PA66, UL94V-0
Clamp: Copper alloy, Sn Plated
Shrapnel: Stainless steel


Electrical
Rated voltage: 300V
Rated current: 8A
Contact Resistance: 20mΩ
Insulation resistance: 500MΩ/DC500V
Withstand voltage: AC2000V / 1min
Wire Range: 24~16AWG 1.0mm²

Mechanical
Temp. Range: -40°C ~ +105°C
Strip length: 9~10mm

Order Information

L-KLS2-FMC-3.81-XXP-4

RoHS
Terminal Block
Pitch: 3.81mm
No. of Pole (02P~24P)
Color: 4 - Green

GENERAL TOLERANCE	ANGLE TOLERANCE	Description:
X. ±0.60	X. ±5°	3.81mm Male Pluggable terminal block
.X ±0.38	.X ±3°	
.XX ±0.25	.XX ±2°	KLS P/N: L-KLS2-FMC-3.81-XXP-4
Draw by 2023-11-22	PROJECTION	 NingBo KLS ELECTRONIC CO.,L TD.
Check by 2023-11-22	UNITS	
SCALE	SHEET SIZE	

