

assembly aid enclosed

SW15  
width across  
flat: 15

A (2:1)  
contact face acc. to  
IEC 61076-2-101

SW18  
width across  
flat: 18

M12x1

M16x1,5

SW19  
width across  
flat: 19

complete length when assembled app. 42

panel  
thickness

Panel cut out  
(1:1)



min.2 - max.5

$\varnothing 16,3 \pm 0,2$

14,3±0,2

recommended torque of counter nut: 2Nm  
order contacts separately

cable $\varnothing$			wire gauge	part-no.
5,7 - 6,9mm	6,5 - 7,7mm	7,5 - 8,8mm		
sealing			AWG 26-22	09 67 000 5476
A	B	C	AWG 24-20	09 67 000 8476
			AWG 22-18	09 67 000 3476



All Dimensions in mm  
Original Size DIN A4

Scale  
1:1

Free size tol.

Ref.  
Sub.



All rights reserved  
Department EL PD

Created by  
BALSAN

Inspected by  
FARCASIU

Standardisation  
ROEBEN

Date  
2021-09-13

State  
Final Release

Title  
M12 PFT Slim Design female D-cod 4-pol

Doc-Key / ECM-Nr.  
100622621/UGD/001/J  
500000202436

HARTING  
D-32339 Espelkamp

Type  
TB

Number  
21038812425

Rev.  
J

Page  
1/1