



Type Designation	4920
Designation IEC	LR20
System	Zn-MnO <sub>2</sub> (Alkaline)
Shelf Life (Coding)*	10 years
Nominal Voltage [V]	1.5
Typical Capacity C [mAh]	16500 (discharge with high-resistance)
Permissible Temperature Range	- 10 °C ... 50 °C
Weight, approx. [g]	136,9
Volume [ccm]	51.3

Dimensions [mm] min: max:

∅	32.3	34.2
A	-	61.5
B	59.5	-
C	18.0	-
E	-	1.0
F	-	9.5
G	1.5	-

**Typical Capacities (at 20°C):**



Discharge Type	Load	End Voltage[V]	0.9
4M/15M,8H/D,7D/W	2.2 Ω	Time [h]	25,3
Portable lighting		Capacity [Ah]	13,0
		Energy [Wh]	14,8
Discharge Type	Load	End Voltage[V]	0.8
1H/D,7D/W	2.2 Ω	Time [h]	29,1
Toy		Capacity [Ah]	13,9
		Energy [Wh]	14,9
Discharge Type	Load	End Voltage[V]	0.9
2H/D,7D/W	600 mA	Time [h]	16,0
Portable Stereo		Capacity [Ah]	9,5
		Energy [Wh]	10,3

**No publication or circulation of data to third parties without consent of VARTA Consumer Batteries**

\* In consideration of typical loss of capacity at storage and application.