

Specifications	Range	Best Accuracy
Model	?	UT210E
AC Current (A)	2A/20A/100A	±(2.5%+5)
DC Current (A)	2A/20A/100A	±(2%+3)
AC Voltage (V)	2V/20V/200V/600V	±(1%+3)
DC Voltage (V)	200mV/2V/20V/200V/600V	±(0.7%+3)
Resistance (?)	200?/2k?/20k?/200k?/2M?/20M?	±(1%+2)
Capacitance (F)	2nF/20nF/200nF/2?F /20?F/200?F/2mF/20mF	±(4%+5)
Features		
Display Count	?	2000
Auto Range	?	?
Jaw Capacity	?	17mm
True RMS	?	?
Diode	Around 3.0V	?
V.F.C.	?	?
NCV	?	?
Auto Power Off	Around 15 minutes	?
Continuity Buzzer	?	?
Low Battery Indication	?2.5V	?
Data Hold	?	?
Zero Mode	?	?

MAX/MIN	?	?
LCD Backlight	?	?
Input Protection	?	?
Input Impedance for DCV	?10M?	?
General Characteristics		
Power	AAA 1.5V x 2	
LCD Size	39.3mm x 26.5mm	
Product Color	Red and grey	
Product Net Weight	170g	
Product Size	175mm x 60mm x 33.5mm	
Standard Accessories	Batteries, Test Lead	
Standard Individual Packing	Gift Box, Carrying bag, English Manual	
Standard Quantity Per Carton	40pcs	
Standard Carton Measurement	385mm x 345mm x 305mm (0.041 CBM Per Standard Carton)	
Standard Carton Gross Weight	11kg	