

Specifications	Range	Best Accuracy
Model	?	UT216D
AC Current (A)	60A/600A	±(2.5%+5)
AC Current Frequency (Hz)	?	40Hz ~ 400Hz
DC Current (A)	60A/600A	±(2.5%+5)
AC Voltage (V)	6V/60V/600V/750V	±(1.2%+5)
AC Current Frequency (Hz)	?	40Hz ~400Hz
DC Voltage (V)	600mV/6V/60V/600V/1000V	±(0.8%+1)
Resistance (Ω)	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(1%+2)
Capacitance (nF)	99.99nF/999.9nF/9.999μF/99.99μF/999.9μF/9.999mF/60mF	±(4.0%+5)
Frequency (Hz)		
Temperature (°C)	-40°C ? 1000°C	±(2.0%+5)
Temperature (°F)	-40°F ? 1832°F	±(2.0%+10)
Features		
Display Count	?	6000
Auto Range	?	?
Jaw Capacity	?	30mm
True RMS	?	?
Diode	Around 3.0V	?
VFC	?	?
NCV	?	?

Data Hold	?	?
Relative Mode	?	?
MAX/MIN	?	?
Inrush Current	?	?
LCD Backlight	?	?
OLED Display	?	?
Analogue Bar Graph	?	21
Flashlight	?	?
Auto Power Off	Around 15 minutes	?
Continuity Buzzer	?	?
Low Battery Indication	?3.6V	?
Input Protection	?	?
Input Impedance for DCV	?10M?	?
General Characteristics		
Power	AAA 1.5V x 3	
LCD Size	38mm x 24 mm	
Product Color	Red and Grey	
Product Net Weight	231.7g	
Product Size	220mm x 75mm x 40mm	
Standard Accessories	Batteries, Test Lead, Point Contact Temperature Probe	
Standard Individual Packing	Gift Box, Carrying Bag, English Manual	
Standard Quantity Per Carton	40pcs	

Standard Carton Measurement	485mm x 320mm x 385mm
Standard Carton Gross Weight	20kg