



Part Number : [5600850101](#)
Product Description : DuraClik Crimp Terminal, Female, 26-22 AWG, Reel
Series Number : 560085
Status : Active
Product Category : Crimp Terminals



Documents & Resources

Drawings

[5600850101_sd.pdf](#)
[PK-560085-001-001.pdf](#)

Specifications


[AS-560085-001-JP-001.pdf](#)

Tooling Specifications

[571753710ATS-000.pdf](#)
[571753710ATS-J-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 44
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Crimp Terminals
Series	560085
Description	DuraClik Crimp Terminal, Female, 26-22 AWG, Reel
Application	Automotive, Power, Signal, Wire-to-Board
Product Name	DuraClik
UPC	887191151892

Electrical

Voltage - Maximum	125V
-------------------	------

Physical

Gender	Female
Material - Metal	Phosphor Bronze
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	0.049/g
Packaging Type	Reel
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	1.40mm
Wire Size (AWG)	22, 24, 26
Wire Size mm ²	0.34

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

Use with Part(s)

Description	Part Number
DuraClik Single Row Receptacle Housings	<u>502351</u>

Application Tooling

Global

Description	Part Number
Extraction Tool for Micro-Fit Terminals	<u>11030043</u>
FineAdjust Applicator for 2.00mm Pitch Wire-to-Board Crimp Receptacle Terminal and SMEC Crimp Receptacle Terminals, 26-22 AWG and AVSS 0.3 Wires	<u>2037021900</u>
PremiumGrade Hand Crimp Tool for Micro-Latch, DuraClik, and Servo Motor Encoder Female Terminals, 26-22 AWG	<u>638235100</u>
