



EMP-350A-D-D-OR-XX

7

6

未注公差/General tolerances(mm)												0.1/10		
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400		>400 ~ 500	>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2°

技术要求/Technical requirements:	
额定电压电流/Rated Voltage/Current	1500V/350A
接触阻抗/Contact resistance	≤0.25mΩ
绝缘电阻/Insulation resistance	5000 MΩ MIN (Drying) 200MΩ MIN (RH 95%)
耐电压/Withstanding voltage	POWER CONTACT: 4000V AC; HVIL CONTACT: 600V AC
防水等级/Levels of protection	IP67 (Matching state)
盐雾要求/Salt Spray	240h (Matching state)
机械寿命/Mechanical cycle	200 Cycling
阻燃等级/Flame retardant rating	UL94-V0
使用温度范围/Operating temperature(° C)	-40~+125
符合RoHS环保要求/Conform to RoHS	Yes
认证信息/Certification	UL, TUV

6. Color  
OR--orange

7. Serial number reference  
XX=HV or 00 , 01 , 02 , 03 .....99  
HV--with interlock pin  
00--without interlock pin  
"01 , 02 , 03 .....99--No constructional differences.  
Models differ only in model name and marking label"

		MATERIAL: 材质	SURFACE/COLOR: 表面处理		
APPD:		MAT NO./REV: 物料编码 / 版本	MAT STATUS: 物料状态		
CHKD:		NAME: EMP-350A-D-D-OR-XX			
DRFT:	Chen Q	2024.1.18	DRAWING NO.	TYPE	DRAWING STATUS
REV	ECN	DESCRIPTION	图号	图纸类型	图状态
00	ECN	/	Chen Q	2024.1.18	SCALE
REV	ECN	DESCRIPTION	DRFT	DATE	SCALE
					1:1
					SHEET
					1/1

Transfer or duplication of this document as well as the utilization of its contents without the written permission of DEGSON is prohibited. All rights reserved for patent. 复制或再行发布此文件以及未获得 DEGSON 书面许可而擅自使用其内容均属于侵权行为。DEGSON 保留所有权利。未经许可，不得复制或再行发布此文件。如有侵权，DEGSON 将依法追究法律责任。