


Current Transducer LT 300-T/SP7

$$I_{PN} = 300 \text{ A}$$

For the electronic measurement of currents : DC, AC, pulsed..., with a galvanic isolation between the primary circuit (high power) and the secondary circuit (electronic circuit).



Electrical data

I_{PN}	Primary nominal r.m.s. current	300	A			
I_P	Primary current, measuring range	0 .. ± 500	A			
R_M	Measuring resistance	R_{Mmin}	R_{Mmax}			
				with $\pm 12 \text{ V}$	@ $\pm 300 \text{ A}_{max}$	0
			@ $\pm 500 \text{ A}_{max}$	0	5	Ω
		with $\pm 18 \text{ V}$	@ $\pm 300 \text{ A}_{max}$	20	70	Ω
	@ $\pm 500 \text{ A}_{max}$	20	25	Ω		
I_{SN}	Secondary nominal r.m.s. current	150	mA			
K_N	Conversion ratio	1 : 2000				
V_C	Supply voltage ($\pm 5 \%$)	$\pm 12 .. 18$	V			
I_C	Current consumption	28 (@ $\pm 18 \text{ V}$) + I_S	mA			
V_d	R.m.s. voltage for AC isolation test, 50 Hz, 1 mn	6	kV			

Features

- Closed loop (compensated) current transducer using the Hall effect
- Insulated plastic case recognized according to UL 94-V0.

Special features

- $T_A = -25^\circ\text{C} .. +70^\circ\text{C}$
- Railway equipment.

Advantages

- Excellent accuracy
- Very good linearity
- Low temperature drift
- Optimized response time
- Wide frequency bandwidth
- No insertion losses
- High immunity to external interference
- Current overload capability.

Accuracy - Dynamic performance data

X_G	Overall accuracy @ $I_{PN}, T_A = 25^\circ\text{C}$	± 0.5	%
e_L	Linearity	< 0.1	%
I_O	Offset current @ $I_P = 0, T_A = 25^\circ\text{C}$	Typ	Max
I_{OT}	Thermal drift of I_O - $25^\circ\text{C} .. +70^\circ\text{C}$	± 0.4	± 0.6 mA
t_r	Response time ¹⁾ @ 90 % of I_{Pmax}	< 1	μs
di/dt	di/dt accurately followed	> 50	A/ μs
f	Frequency bandwidth (-1 dB)	DC .. 150	kHz

Applications

- AC variable speed drives and servo motor drives
- Static converters for DC motor drives
- Battery supplied applications
- Uninterruptible Power Supplies (UPS)
- Switched Mode Power Supplies (SMPS)
- Power supplies for welding applications.


General data

T_A	Ambient operating temperature	- 25 .. + 70	$^\circ\text{C}$
T_S	Ambient storage temperature	- 40 .. + 85	$^\circ\text{C}$
R_S	Secondary coil resistance @ $T_A = 70^\circ\text{C}$	35	Ω
m	Mass	480	g
	Standards ²⁾	EN 50155	

Notes : ¹⁾ With a di/dt of 100 A/ μs

²⁾ A list of corresponding tests is available

Dimensions LT 300-T/SP7 (in mm. 1 mm = 0.0394 inch)



Mechanical characteristics

- General tolerance ± 0.3 mm
- Fastening 2 holes $\varnothing 5.5$ mm or by the primary bar
- Connection of primary 2 holes $\varnothing 8.5$ mm
- Connection of secondary Faston 6.3 x 0.8 mm

Remarks

- I_s is positive when I_p flows in the direction of the arrow.
- Temperature of the primary conductor should not exceed 100°C.