

This product is completed the Lead-free &amp; RoHS2.0 &amp; Halogen-free.

Customer : Ozdisan

|             |               |
|-------------|---------------|
| Issued Date | 2025-5-6      |
| No.         | RD20250506001 |

## SPECIFICATION FOR APPROVAL

| No. | Customer No. | Koshin Part No.      | Description | ΦD x L |
|-----|--------------|----------------------|-------------|--------|
| 1   |              | MRW-035V221MF100-T/R | 35V220μF    | 8X10   |

## KOSHIN INTERNATIONAL LIMITED

## Headquarters

Unit 9-10,16/F,New commerce Centre,19 On Sun Street,Siu Lek Yuen,Shatin,N.T.,Hong kong  
TEL: (852) 2690 0609 FAX: (852) 2697 9532

## Manufacturing Sites

☐ No.4-6 West Zone,Shangxue Technology Industrial City,Bantian,Longgang,Shenzhen,China




TEL: +86-755-89500370 89500371 FAX: +86-755-89500348

☒ Koshin Technology Industrial Zone South Huancheng Road,LinWu,Chenzhou,Hunan

Provice,China

TEL: +86-0735-7770828

Postal code:424300

| KOSHIN<br>APPROVED SIGNATURE FOR KOSHIN   |   |   | APPROVED SIGNATURE FOR CUSTOMER |
|---|---|---|---------------------------------|
| APPROVAL  | CHECK   | DESIGN  | APPROVED BY                     |
|  |  |  |                                 |

Please return one copy with your authorized signature when you accept these specifications.

DJS-SD-0013

[illegible]

**CONTENTS**

| NO. | Items   |
|-----|---|
| 1   | Scope   |
| 2   | Operating Temperature Range   |
| 3   | Characteristics   |
| 4   | Frequency Coefficient for Ripple Current                                |
| 5   | Max. Impedance Ratio  |
| 6   | Characteristics Table   |
| 7   | Marking   |
| 8   | Inner conformation drawing and inner constitute parts(curtness drawing) |
| 9   | Recommended soldering heat conditions                                   |
| 10  | Electrical characteristics  |
| 11  | Mechanical characteristics  |
| 12  | Reliability   |
| 13  | Koshin Part No  |
| 14  | Product processing diagram  |
| 15  | Packing   |
| 16  | Guidelines and Precautions  |
|     |   |
|     |   |
|     |   |
|     |   |

## 1. Scope

This specification covers "MRW series" V-Chip Aluminium Electrolytic Capacitors.

## 2. Operating Temperature Range

Operating temperature range is the range of ambient temperature at which the capacitor can be operated continuously at rated voltage.

## 3. Characteristics

Unless otherwise specified, the standard range of atmospheric conditions for making measurements and tests are as follows.

Ambient temperature : 15 to 35°C

Air pressure: 86kpa to 106kpa

If there may be doubt on the results, measurements shall be made within the following limits.

Ambient temperature : 20±2°C

Air pressure: 86kpa to 106kpa

## 4. Frequency Coefficient for Ripple Current

| Case Code | Frequency (Hz)  | 120  | 1K   | 10K  | 100K |
|-----------|-----------------|------|------|------|------|
|           | Capacitance(μF) |      |      |      |      |
| B057-G105 | 1.0             | 1.00 | 1.50 | 1.75 | 1.80 |
|           | 2.2 to 10       | 1.00 | 1.30 | 1.40 | 1.50 |
|           | 22 to 1,500     | 1.00 | 1.05 | 1.08 | 1.08 |

## 5. Max. Impedance Ratio


| Low temperature characteristics | Rated voltage(V)      |   | 6.3 | 10 | 16 | 25 | 35 | 50 | 63 | 100 | 120Hz |
|---------------------------------|-----------------------|---|-----|----|----|----|----|----|----|-----|-------|
|                                 | Impedance ratio (max) | $Z_{(-25^{\circ}\text{C})} / Z_{(+20^{\circ}\text{C})}$ | 4   | 3  | 2  | 2  | 2  | 2  | 2  | 3   |       |
|                                 |                       | $Z_{(-40^{\circ}\text{C})} / Z_{(+20^{\circ}\text{C})}$ | 12  | 8  | 6  | 4  | 3  | 3  | 3  | 4   |       |

## 6.Characteristics Table

| Aluminum Electrolytic Capacitor Specification                           |   |  |     |   |   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
|---|---|--|-----|---|---|---------|-------|---|---|---|---|---|---|---|-------|---|----|-----|-----|-----|-----|---------|
| Series  | MRW   | 35 V 220μF   |     | Part No.                                | MRW-035V221MF100-T/R  |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
| Customer No.  |   |  |     | Case size                               | ΦD 8 X L 10   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
| Specification   | Items   |  |     | Standard                                |   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
|   | Operating temperature range   |  |     | - 40 ~ + 105 ℃                          |   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
|   | Capacitance tolerance   |  |     | ±20% ( 20℃ ,120Hz )                     |   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
|   | Dissipation factor (MAX)  |  |     | 小于( Less than ) 14% ( 20℃ ,120Hz )      |   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
|   | Leakage current (MAX)   |  |     | 小于( Less than ) 77μA ( 20℃ 35 V 2 min ) |   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
|   | ESR (MAX)   |  |     | / Ω ( 100KHz ,20℃ )                     |   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
|   | Ripple current (MAX)  |  |     | 300mArms ( 120Hz ,105℃ )                |   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
|   | Load life   |  |     | 2000 hrs                                |   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
| Outline   | ( Dimensions )  |  |     |   |   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
|   | <div><div><div>8øx10L以上防爆阀</div><div></div></div><div><div></div></div></div>   |  |     |   |   |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
|   | <div>Lead spacing and Diameter<div>Unit: mm</div><table><tr><td>D</td><td>L</td><td>a</td><td>A</td><td>B</td><td>C</td><td>W</td><td>P±0.2</td></tr><tr><td>8</td><td>10</td><td>0.5</td><td>8.3</td><td>8.3</td><td>9.0</td><td>0.7~1.1</td><td>3.1</td></tr></table></div> |  |     |   |   |         |       | D | L | a | A | B | C | W | P±0.2 | 8 | 10 | 0.5 | 8.3 | 8.3 | 9.0 | 0.7~1.1 |
| D   | L   | a  | A   | B                                       | C   | W       | P±0.2 |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
| 8   | 10  | 0.5  | 8.3 | 8.3                                     | 9.0   | 0.7~1.1 | 3.1   |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
| APPROVAL  |   | CHECK  |     |   | DESIGN  |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |
| <div><div>R&amp;D</div><div>May.05.2025</div><div>Alex Shen</div></div> |   | <div><div>R&amp;D</div><div>May.05.2025</div><div>D.S.He</div></div> |     |   | <div><div>R&amp;D</div><div>May.05.2025</div><div>X.L.Kuang</div></div> |         |       |   |   |   |   |   |   |   |       |   |    |     |     |     |     |         |

7. Marking


7.1. Marking on capacitors includes:



Year Code

|      |      |      |      |      |      |      |      |      |      |
|------|------|------|------|------|------|------|------|------|------|
| Year | 2022 | 2023 | 2024 | 2025 | 2026 | 2027 | 2028 | 2029 | 2030 |
| Code | N    | P    | R    | S    | T    | V    | W    | X    | Y    |

8. Inner conformation drawing and inner constitute parts(curtness drawing)




| Composing Part | Material      |
|----------------|---------------|
| Lead Wire      | Fe+Al+Cu+Sn   |
| Case           | Aluminum      |
| Base Plate     | PPA           |
| Paper          | Cellulose     |
| Anode Foil     | Aluminum Foil |
| Cathode Foil   | Aluminum Foil |
| Electrolyte    | GBL           |
| Seal           | Rubber        |
| Glue/Tape      | Poly/OPP      |

9.Recommended soldering heat conditions:

RECOMMEDEDSOLDERINGCONDITIONSFORALUMINIUM  
SURFACE MOUNT TYPE

-Air or Infrared reflow soldering





| SMDshape | size      | voltage       | preheating             | Time maintained over 217 °C | Time maintained over 230 °C | Peak temperature | Reflow number |
|----------|-----------|---------------|------------------------|-----------------------------|-----------------------------|------------------|---------------|
|          | B52~E87   | 4~63V         | 150 - 180C<br>≤120Sec. | ≤90 Sec                     | ≤60 Sec                     | ≤260 °C          | ≤2 times      |
|          |           | 63V,80V       |                        | ≤60 Sec                     | ≤40 Sec                     | ≤250 °C          | ≤2 times      |
|          | F63~G100  | 4~50V         |                        | ≤60 Sec                     | ≤30 Sec                     | ≤245 °C          | ≤2 times      |
|          |           | 63V~100, 400V |                        | ≤30 Sec                     | ≤20 Sec                     | ≤240 °C          | ≤2 times      |
|          | H135~K215 | 6.3~50V       |                        | ≤30 Sec                     | ≤20 Sec                     | ≤240 °C          | ≤2 times      |
|          |           | 63~450V       |                        | ≤20 Sec                     | —                           | ≤230 °C          | ≤2 times      |

Remark: Reflow number cannot over 2 times. After first time reflow , must be ensure that the temperature of capacitors became cold to room temperature(5~35℃) ,then continue second flow.



### 10. Electrical characteristics:

| NO.  | ITEM                                | TEST METHOD   |                                 |                      | SPECIFICATION   |
|------|-------------------------------------|---|---------------------------------|----------------------|---|
| 10.1 | Rated voltage                       | Voltage: DC voltage + peak ripple voltage $\leq$ Rated voltage  |                                 |                      | See 6.Characteristics Table   |
| 10.2 | Capacitance                         | 1.Measuring frequency:120Hz $\pm$ 12Hz<br>2.Measuring voltage: $\leq 0.5V_{rms} + 0.5V_{DC} \sim 2.0V_{DC}$<br>3.Measuring circuit: (  )  |                                 |                      | See 6.Characteristics Table   |
| 10.3 | Dissipation factor                  |   |                                 |                      | See 6.Characteristics Table   |
| 10.4 | Leakage current                     | DC leakage current shall be measured after 1~2minutes application of the DC rated working voltage through the 1000 $\Omega$ resistor at 20°C<br>在 20°C<br><br><div style="display: flex; justify-content: space-around; margin-top: 10px;"> <div> <p>R: 1000 <math>\Omega</math></p> <p>A: DC current meter</p> <p>V: DC voltage meter</p> </div> <div> <p>S1: Switch</p> <p>S2: Switch for protect of current meter</p> <p>C<sub>x</sub>: Testing capacitor</p> </div> </div> |                                 |                      | 4X5.7-10X10.5,6.3V-100V<br>Less than 0.01CV or 3 $\mu$ A,<br>whichever is large ( at 20°C,<br>2 minutes)<br><br>12.5X13.5-18X21.5,10-100V<br>Less than 0.03CV or 4 $\mu$ A,<br>whichever is large ( at 20°C,<br>1minutes)<br><br>I: Leakage current( $\mu$ A)<br>C: Capacitance( $\mu$ F)<br>V: Rated voltage (V) |
| 10.5 | Temperature characteristics<br>温度特性 | STEP<br>步骤  | TEMPERATURE<br>温度               | STORAGE TIME<br>放置时间 | Step2.<br>Low temperature<br>impedance stability<br>Less than specified value.<br><br>Step4.<br>Capacitance change:<br>within $\pm 10\%$ of the initial<br>measured value.<br><br>Dissipation factor:<br><br>Less than specified value.   |
|      |                                     | 1   | 20°C $\pm$ 2°C                  | 30minutes            |   |
|      |                                     | 2   | -40°C $\pm$ 3°C -55°C $\pm$ 3°C | 2hours               |   |
|      |                                     | 3   | 20°C $\pm$ 2°C                  | 4hours               |   |
|      |                                     | 4   | 105°C $\pm$ 2°C                 | 2hours               |   |
|      |                                     | Step1.Measure the capacitance and impedance.<br>( Z , 20°C,120Hz $\pm$ 2HZ )<br><br>Step2. Measure the impedance at thermal balance after 2 hours.<br>( Z , -40°C -55°C 120Hz $\pm$ 2HZ )<br><br>Step4.Measure the leakage current at thermal balance after 2 hours   |                                 |                      |   |

| NO.                           | ITEM       | TEST METHOD  | SPECIFICATION                 |     |    |    |    |     |     |    |    |     |                              |   |    |    |    |    |    |    |     |     |   |
|-------------------------------|------------|--|-------------------------------|-----|----|----|----|-----|-----|----|----|-----|------------------------------|---|----|----|----|----|----|----|-----|-----|---|
| 10.6                          | Surge test | <p>Rated surge voltage shall be applied (switch on)for 30±5 second and then shall be applied (switch off) with discharge for 5.5min at room temperature. This cycle shall be repeated for 1000 cycles. Duration of one cycle is 6±0.5 minutes</p> <p>Surge voltage</p> <table><tr><td>Working voltage(V)<br/>工作电压(V)</td><td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td><td>63</td><td>80</td><td>100</td></tr><tr><td>Surge voltage (V)<br/>浪涌电压(V)</td><td>8</td><td>13</td><td>20</td><td>32</td><td>44</td><td>63</td><td>79</td><td>100</td><td>125</td></tr></table> | Working voltage(V)<br>工作电压(V) | 6.3 | 10 | 16 | 25 | 35  | 50  | 63 | 80 | 100 | Surge voltage (V)<br>浪涌电压(V) | 8 | 13 | 20 | 32 | 44 | 63 | 79 | 100 | 125 | <p>Capacitance change:<br/>within±15% of the initial specified value.</p> <p>Dissipation factor:<br/>Less than specified value.</p> <p>Leakage current:<br/>Within initial specified value.</p> |
| Working voltage(V)<br>工作电压(V) | 6.3        | 10   | 16                            | 25  | 35 | 50 | 63 | 80  | 100 |    |    |     |                              |   |    |    |    |    |    |    |     |     |   |
| Surge voltage (V)<br>浪涌电压(V)  | 8          | 13   | 20                            | 32  | 44 | 63 | 79 | 100 | 125 |    |    |     |                              |   |    |    |    |    |    |    |     |     |   |


### 11.Mechanical characteristics:

| NO.      | ITEM          | TEST METHOD  | SPECIFICATION |      |           |            |          |     |     |     |       |      |           |            |          |     |     |     |  |
|----------|---------------|--|---------------|------|-----------|------------|----------|-----|-----|-----|-------|------|-----------|------------|----------|-----|-----|-----|--|
| 11.1     | Lead strength | <p>(A)Tensile strength:<br/>wire lead terminal:</p> <table border="1"> <tr> <td>d(mm)</td><td>≤0.5</td><td>0.5&lt;d≤0.8</td><td>0.8&lt;d≤1.25</td></tr> <tr> <td>load(kg)</td><td>0.5</td><td>1.0</td><td>2.0</td></tr> </table> <p>The capacitor shall withstand the constant tensile force specified between the body and each lead for 10seconds without damage either mechanical or electrical.</p> <p>(B) Bending strength:<br/>wire lead terminal:</p> <table border="1"> <tr> <td>d(mm)</td><td>≤0.5</td><td>0.5&lt;d≤0.8</td><td>0.8&lt;d≤1.25</td></tr> <tr> <td>load(kg)</td><td>0.5</td><td>0.5</td><td>1.0</td></tr> </table> <p>with the capacitor in a vertical position apply the load specified axially to each lead. The capacitor shall be rotated slowly from the vertical to the horizontal position, back to the vertical position. The 90 ° in the opposite direction and back the original position. Performance of capacitor shall not have change and leads shall be undamaged.</p> | d(mm)         | ≤0.5 | 0.5<d≤0.8 | 0.8<d≤1.25 | load(kg) | 0.5 | 1.0 | 2.0 | d(mm) | ≤0.5 | 0.5<d≤0.8 | 0.8<d≤1.25 | load(kg) | 0.5 | 0.5 | 1.0 | <p>When the capacitance is measured, there shall be no intermittent contacts, or open-or short-circuiting.</p> <p>There shall be no such mechanical damage as terminal damage etc.</p> |
| d(mm)    | ≤0.5          | 0.5<d≤0.8  | 0.8<d≤1.25    |      |           |            |          |     |     |     |       |      |           |            |          |     |     |     |  |
| load(kg) | 0.5           | 1.0  | 2.0           |      |           |            |          |     |     |     |       |      |           |            |          |     |     |     |  |
| d(mm)    | ≤0.5          | 0.5<d≤0.8  | 0.8<d≤1.25    |      |           |            |          |     |     |     |       |      |           |            |          |     |     |     |  |
| load(kg) | 0.5           | 0.5  | 1.0           |      |           |            |          |     |     |     |       |      |           |            |          |     |     |     |  |

| NO.  | ITEM                 | TEST METHOD  | SPECIFICATION  |
|------|----------------------|--|--|
| 11.2 | Vibration resistance | The frequency of the vibration shall vary uniformly within the range 10 to 55 Hz with the amplitude of 0.75mm, completing the cycle in the internal of one minute.<br>The capacitor shall be securely mounted by its leads with hold the body of capacitor.<br>The capacitor shall be vibrated in three mutually perpendicular directions for a period of 2 hours in each direction. | Capacitance: no unsteady.<br><br>Appearance: no abnormal.<br><br>Capacitance change: within $\pm 5\%$ of initial measured value. |
| 11.3 | Solder-ability       | The leads are dipped in the solder bath of Sn at $235^{\circ}\text{C}\pm 5^{\circ}\text{C}$ for $2\pm 0.5$ seconds. The dipping depth should be set at 1.5~2.0 mm.   | The solder alloy shall cover the 95% or more of dipped lead's area.  |

### 12. Reliability:

| NO.  | ITEM                      | TEST METHOD   | SPECIFICATION   |
|------|---------------------------|---|---|
| 12.1 | Soldering heat resistance | The leads immerse in the solder bath of Sn at $260^{\circ}\text{C}\pm 5^{\circ}\text{C}$ for $10\pm 1$ seconds until a distance of 1.5~2.0mm from the case. | No visible damage or leakage of electrolyte.<br><br>Capacitance change: Within $\pm 5\%$ of the initial measured value<br><br>Tan $\delta$ : Less than specified value.<br><br>Leakage current: Less than specified value |
| 12.2 | Moisture Resistance       | Subject the capacitor to $40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and 90% to 95% relative humidity for 504 hours.   | Capacitance change: Within $\pm 20\%$ of the initial measured value<br><br>Tan $\delta$ : Less than 1.2 specified value.<br><br>Leakage current: Less than specified value  |

| NO.  | ITEM                       | TEST METHOD   | SPECIFICATION   |
|------|----------------------------|---|---|
| 12.3 | Load life                  | After 2000 hours continuous application of DC rated working voltage and rated ripple current at $105^{\circ}\text{C} \pm 2^{\circ}\text{C}$ , Measurements shall be performed after 16 hours exposed at room temperature.   | Capacitance change:<br>within $\pm 20\%$ of the initial specified value.<br><br>Dissipation factor:<br>Less than 200% of the initial specified value.   |
| 12.4 | Shelf life                 | After storage for 1000 hours at $105^{\circ}\text{C} \pm 2^{\circ}\text{C}$ without voltage application, Measurements shall be performed after exposed for 16 hrs at room temperature after application of Testing  | Leakage current:<br>Within initial specified value.   |
| 12.5 | Storage at low temperature | The capacitor shall be stored at temperature of $-40^{\circ}\text{C} \pm 3^{\circ}\text{C}$ for 16 hours, during which time be subjected to standard atmospheric conditions for 16 hours or more. After which measurements shall be made.   | Capacitance change:<br>Within $\pm 10\%$ of the initial value.<br><br>Tan $\delta$ :less than specified value<br><br>Leakage current:<br>Less than specified value.<br><br>Appearance :no Abnormal.   |
| 12.6 | Pressure relief            | <p>DC test<br/>Send the following electricity while applying the inverse voltage.</p> <p>Where case size<br/> <math>D \leq 22.4\text{mm}</math>: 1 A d.c.max<br/> <math>D &gt; 22.4\text{mm}</math>: 10 A d.c.max</p> <p>Note: 1.This requirement applies to capacitors with a diameter of 6 mm or more.<br/> 2. When the pressure relief device does not open even 30 minutes after commencement of test, the test may be ended.</p> | <p>DC test circuit</p>  <p>S : Switch<br/> Ⓐ : DC current meter<br/> Cx: testing capacitor</p> <p>The pressure relief device shall open in such a way as to avoid any damage of fire or explosion of capacitor elements (terminal and metal foil etc.) or cover.</p> |

## 13.Koshin Part No

## Part Number System

MRW-035V 221 M F 100 - T/R

① ② ③ ④ ⑤ ⑥ ⑦

## (1) Series

|     |     |     |     |     |     |     |     |     |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| MRS | MRW | MRH | MRL | MRB | MRN | MRE | MRA | MRF | MRT |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|

## (2) Voltage(WV)

|             |     |     |     |     |     |     |     |     |     |     |     |     |
|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Voltage(WV) | 4   | 6.3 | 10  | 16  | 25  | 35  | 50  | 63  | 80  | 100 | 110 | 115 |
| Code        | 004 | 6R3 | 010 | 016 | 025 | 035 | 050 | 063 | 080 | 100 | 110 | 115 |

|             |     |     |     |     |     |     |     |     |     |     |     |     |
|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Voltage(WV) | 125 | 160 | 165 | 200 | 220 | 250 | 330 | 350 | 400 | 450 | 500 | 550 |
| Code        | 125 | 160 | 165 | 200 | 220 | 250 | 330 | 350 | 400 | 450 | 500 | 550 |

## (3) Capacitance

Capacitance is show in microfarads ( $\mu\text{F}$ )

|               |     |      |     |     |     |     |      |       |
|---------------|-----|------|-----|-----|-----|-----|------|-------|
| $\mu\text{F}$ | 0.1 | 0.47 | 1   | 2.2 | 22  | 220 | 2200 | 22000 |
| Code          | 0R1 | R47  | 010 | 2R2 | 220 | 221 | 222  | 223   |

## (4) Capacitance tolerance

|             |         |          |          |          |            |           |            |             |
|-------------|---------|----------|----------|----------|------------|-----------|------------|-------------|
| Tolerance % | $\pm 5$ | $\pm 10$ | $\pm 15$ | $\pm 20$ | -0 to +100 | -0 to +20 | -10 to +20 | -10 to +100 |
| Code        | J       | K        | L        | M        | P          | R         | V          | W           |

|             |            |            |            |           |           |           |            |           |
|-------------|------------|------------|------------|-----------|-----------|-----------|------------|-----------|
| Tolerance % | -15 to +20 | -20 to +40 | -20 to +80 | -20 to +5 | +5 to +20 | -10 to +5 | -30 to +20 | -15 to +5 |
| Code        | N          | X          | E          | A         | B         | C         | D          | F         |

## (5) Case (D: mm)

|          |   |   |     |   |    |      |    |    |
|----------|---|---|-----|---|----|------|----|----|
| Diameter | 4 | 5 | 6.3 | 8 | 10 | 12.5 | 16 | 18 |
| Code     | B | C | E   | F | G  | H    | J  | K  |

## (6) Case (L: mm)


|             |     |     |     |      |     |      |     |     |     |     |     |     |     |     |     |     |
|-------------|-----|-----|-----|------|-----|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Description | 5   | 7   | 11  | 12.5 | 25  | 35.5 | 40  | 100 | 110 | 111 | 120 | 130 | 140 | 150 | 220 | 250 |
| Code        | 050 | 070 | 110 | 125  | 250 | 355  | 400 | A00 | A10 | A11 | A20 | A30 | A40 | A50 | B20 | B50 |

## (7) Lead treatment

|             |              |
|-------------|--------------|
| Description | Reel Packing |
| Code        | T/R          |


14.Product processing diagram:

14.1.Product size drawing:



| $\Phi D$ | L       | a   | A    | B    | C    | W       | P $\pm 0.2$ |
|----------|---------|-----|------|------|------|---------|-------------|
| 5        | 5.7     | 0.5 | 5.3  | 5.3  | 5.9  | 0.5~0.8 | 1.4         |
| 6.3      | 5.4/5.7 | 0.5 | 6.6  | 6.6  | 7.2  | 0.5~0.8 | 1.9         |
| 6.3      | 7.7     | 0.5 | 6.6  | 6.6  | 7.2  | 0.5~0.8 | 1.9         |
| 8        | 7       | 0.5 | 8.3  | 8.3  | 9.0  | 0.7~1.1 | 3.1         |
| 8        | 10.5    | 0.5 | 8.3  | 8.3  | 9.0  | 0.7~1.1 | 3.1         |
| 10       | 10.5    | 0.5 | 10.3 | 10.3 | 11.0 | 0.7~1.1 | 4.7         |
| 12.5     | 13.5    | 1.0 | 13.0 | 13.0 | 13.7 | 1.0~1.3 | 4.2         |
| 12.5     | 16.5    | 1.0 | 13.0 | 13.0 | 13.7 | 1.0~1.3 | 4.2         |
| 16       | 16.5    | 1.0 | 17.0 | 17.0 | 18.0 | 1.0~1.3 | 6.5         |
| 16       | 21.5    | 1.0 | 17.0 | 17.0 | 18.0 | 1.0~1.3 | 6.5         |
| 18       | 16.5    | 1.0 | 19.0 | 19.0 | 20.0 | 1.0-1.3 | 6.5         |
| 18       | 21.5    | 1.0 | 19.0 | 19.0 | 20.0 | 1.0-1.3 | 6.5         |

14.2 Land/Pad Pattern



| unit: mm       |     |     |     |
|----------------|-----|-----|-----|
| Size           | a   | b   | c   |
| C052,C057      | 1.4 | 3.0 | 1.6 |
| E052,E057,E077 | 1.9 | 3.5 | 1.6 |
| F063           | 2.3 | 4.5 | 1.6 |
| F100           | 3.1 | 4.2 | 2.2 |
| G100           | 4.5 | 4.4 | 2.2 |
| H135,H160      | 4.0 | 5.7 | 2.5 |
| J165,J215      | 6.0 | 6.9 | 2.5 |
| K165,K215      | 6.0 | 7.9 | 2.5 |

### 15.Packing

#### 15.1 Taping Specification for SMD Type

##### 15.1.1 Carrier Tape




Fig. 1-1






Fig. 1-2

Unit: mm


| $\phi$ DXL  | A         | B         | $\phi$ d  | F         | P         | P1        | P2        | t1  | t2        | W         | W1         | Fig.No. |
|-------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----|-----------|-----------|------------|---------|
|             | $\pm 0.2$ | $\pm 0.2$ | $\pm 0.1$ | $\pm 0.1$ | $\pm 0.1$ | $\pm 0.1$ | $\pm 0.1$ | max | $\pm 0.2$ | $\pm 0.3$ | $\pm 0.15$ |         |
| 5X5.7       | 5.7       | 5.7       | 1.5       | 5.5       | 12        | 2.0       | 4.0       | 0.6 | 6.3       | 12        | 1.75       | 1-1     |
| 6.3X5.4/5.7 | 7.0       | 7.0       | 1.5       | 7.5       | 12        | 2.0       | 4.0       | 0.6 | 6.3       | 16        | 1.75       | 1-1     |
| 6.3X7.7     | 7.0       | 7.0       | 1.5       | 7.5       | 12        | 2.0       | 4.0       | 0.6 | 8.3       | 16        | 1.75       | 1-1     |
| 8X7         | 8.7       | 8.7       | 1.5       | 11.5      | 16        | 2.0       | 4.0       | 0.6 | 8.8       | 24        | 1.75       | 1-1     |
| 8X10.5      | 8.7       | 8.7       | 1.5       | 11.5      | 16        | 2.0       | 4.0       | 0.6 | 11.0      | 24        | 1.75       | 1-1     |
| 10X10.5     | 10.7      | 10.7      | 1.5       | 11.5      | 16        | 2.0       | 4.0       | 0.6 | 11.0      | 24        | 1.75       | 1-1     |
| 12.5X13.5   | 13.4      | 13.4      | 1.5       | 14.2      | 24        | 2.0       | 4.0       | 0.6 | 15        | 32        | 1.75       | 1-2     |
| 12.5X16.5   | 13.4      | 13.4      | 1.5       | 14.2      | 24        | 2.0       | 4.0       | 0.6 | 17.5      | 32        | 1.75       | 1-2     |
| 16X16.5     | 17.5      | 17.5      | 1.5       | 20.2      | 28        | 2.0       | 4.0       | 0.5 | 17.5      | 44        | 1.75       | 1-2     |
| 16X21.5     | 17.5      | 17.5      | 1.5       | 20.2      | 28        | 2.0       | 4.0       | 0.5 | 22.5      | 44        | 1.75       | 1-2     |
| 18X16.5     | 19.5      | 19.5      | 1.5       | 20.2      | 32        | 2.0       | 4.0       | 0.5 | 17.5      | 44        | 1.75       | 1-2     |
| 18X21.5     | 19.5      | 19.5      | 1.5       | 20.2      | 32        | 2.0       | 4.0       | 0.5 | 22.5      | 44        | 1.75       | 1-2     |

##### 15.1.2 Reel Package



| Case size | $\Phi$ 5 | $\Phi$ 6.3 | $\Phi$ 8x7 | $\Phi$ 8x8~12.5 | $\Phi$ 10 | $\Phi$ 12.5 | $\Phi$ 16~18 |
|-----------|----------|------------|------------|-----------------|-----------|-------------|--------------|
| W         | 14       | 18         | 18         | 26              | 26        | 34          | 46           |
| A         | 380      | 380        | 380        | 380             | 380       | 380         | 380          |
| t         | 3.0      | 3.0        | 3.0        | 3.0             | 3.0       | 3.0         | 3.0          |

15.1.3 Packing specification




| Product size | Carton size ±2 (mm) |     |     | Q'ty / Reel | Q'ty / Box |
|--------------|---------------------|-----|-----|-------------|------------|
|              | L                   | W   | H   |             |            |
| 5X5.2~7      | 410                 | 410 | 285 | 1000        | 12000      |
| 6.3X5.2~7.7  | 410                 | 410 | 285 | 1000        | 10000      |
| 6.3X11       | 410                 | 410 | 285 | 500         | 5000       |
| 8X6.5~11     | 410                 | 410 | 285 | 500         | 4000       |
| 8X12         | 410                 | 410 | 285 | 400         | 3200       |
| 10X8~10.5    | 410                 | 410 | 285 | 500         | 4000       |
| 10X13.5      | 410                 | 410 | 285 | 400         | 3200       |
| 12.5X13.5    | 410                 | 410 | 285 | 200         | 1200       |
| 18X16.5      | 410                 | 410 | 285 | 125         | 500        |

15.1.4 Label:

| Series | Size(mm) | Sample       |
|--------|----------|--------------|
| Label  | 90×40    | As the right |

| Koshin Electrolytic Capacitors |                      |
|--------------------------------|----------------------|
| OPN:                           | ×××× ②               |
|                                | ③ ⑧                  |
| Type:                          | ⑤⑥⑦ Qty: ⑨ pcs       |
| CPN:                           | ④ Work order number: |
| ①                              | ⑩                    |



KS2020011302460

- ①Customer name
- ②D/C
- ③Koshin Part No.
- ④ Customer Part No.
- ⑤Series
- ⑥Voltage
- ⑦Capacity
- ⑧Size
- ⑨Quantity
- ⑩Work order number




### 15.1.5 Sealing Tape Reel Strength

15.1.5.1 Peel angle: 165 to 180°C referred to the surface on which the tape is glued


15.1.5.2 Peel speed: 300mm per minutes

15.1.5.3 The peel strength must be 0.1 ~ 0.7N under these conditions.




### 15.1.6 Taping method and polarity

#### 15.1.6.1 5、6、8 phi



#### 15.1.6.2 10 phi



### Cautions for Using Aluminum Electrolytic Capacitors

1. When reverse voltage is applied on DC aluminum electrolytic capacitor, the circuit will be short out and the capacitor will be damaged due to abnormal current flows through the capacitor. Please use non-polar types of capacitors when the positive voltage is applied on the cathode terminal.
2. When capacitor is used at higher voltage than the rated voltage, leakage current increased, characteristics drastically deteriorated and damaged in a short period may occur as a result. Please take extra caution that the peak voltage should not exceed the rated voltage.
3. Sudden charge and discharge  
When aluminum electrolytic capacitors for general purpose-use are employed in rapid charge and discharge application, its life expectancy may be shortened resulted from capacitance decrease, heat rise, etc.
4. Storage of the capacitor
  - ① We recommend the following conditions for storage:  
Ambient temperature: 5~35°C, Ambient humidity: <75%RH;
    - a) Storage life: ≤ 12 months;
    - b) **If storage life >12 months, the products need to be charged again before using;**
    - c) If Storage time >three years, the products need to be discarded;
    - d) Expiry Date: calculating from the date marked on the sleeve;
    - e) Please keep capacitors in the original package;
    - f) Avoid storing the capacitors under such circumstances:
      - ※ With water and oil or damp & dewing location.
      - ※ With gas and oil.
      - ※ With toxic gases such as hydrogen sulfide, sulfurous acid, nitrous acid, chlorine, bromine and methane.
      - ※ With direct sunlight, Ozone, ultraviolet rays or radiation.
5. If excessive ripple current is applied on the capacitor, excessive heat will be generated inside, the capacitance will be reduced and capacitor's life shall be shortened. Rated voltage has been marked on the capacitor; therefore, the peak value of the ripple voltage should be less than the rated voltage.
6. Ambient temperature  
Life of aluminum electrolytic capacitor is affected by the ambient temperature. It is generally known that the life doubles for each 10°C decrease in temperature.
7. Tensile strength of lead wire  
When a strong force is applied to the lead wires or terminals, stress is put on the internal connections, which may result in short circuit, open circuit or increased leakage current. So it is not advisable to bend or handle a capacitor after it has been soldered to the PC board.
8. Heat resistance at the soldering process  
During soldering process, secondary shrinkage or sleeve crack may occur when soldering temperature is too high or soldering time is too long.

### 9. Hole pitch and position of PC board

When designig a PC board , its hole pitch should be designed to coincide with the lead pitch(lead spacing) of the capacitor specified in the catalog or specifications. When a capacitor is forcibly inserted into an unmatched hole pitch, a force will put on the leads and which could result in a short circuit or increased leakage current.

### 10. Cleaning after soldering

① The aluminum electrolyte capacitors should be free halogenated solvents during board cleaning after soldering. Use solvent proof capacitors when halogenated solvents are used.

② After cleaned with the solvent which should proof the quality of capacitors, the capacitors should not be kept in solvent environments of non-ventilated places. Let the capacitors after cleaning dry with hot blast fully above 10mins and the temperature of hot blast should not be over than specified upper limit of capacitors.

### 11. Adhesives、fixative and coating materials(coating agent)

① Do not use halogenated adhesives and coating materials to fix aluminum electrolytic capacitors.

② Do not cover up all the sealing area of capacitors with adhesives 、fixative or coating materials(coating agent), make coverage only partial

### 12. Certificates

① ISO 9001:2015

② ISO 14001:2015

③ ISO/IATF 16949:2016

④ OHSAS 45001:2016

### ※ 符合 RoHS2.0 RoHS compliance

**Accord with the latest standard of RoHS2.0 , if customers have any special requirments, according to the relevant agreements which signed by both parts.**