



东莞市润达散热风扇有限公司
Dongguan RUNDA Cooling Fan Co.,Ltd.

样品承认书(Specification)

客户名称(Customer) : _____

品 名(Part Name): DC Brushless Fan

规格型号(Model No.): RD1238B24H-RPS

样品数量(Quantity) : _____

日 期(Date) : 2025-6-23

客户审核 CUSTOMER APPROVED	客户确认 CUSTOMER CHECKED

SUPPLIER: Dongguan RUNDA Cooling Fan Co.,Ltd.

ADD: No.371, Baoling Road, Pingshan Village, Tangxia Town, Dongguan city

TEL: +86-769-82553188

FAX: +86-769-82553118

Website: [Http://www.szrunda.com](http://www.szrunda.com)

APPROVED		CHECKED		PREPARED	
----------	--	---------	--	----------	--

RD-QR-JS04A/2

第 1 页

1.General Specification


项目 Item	描述 Description	测试条件 Condition
1-1. 外形尺寸 Dimension	120x120x38mm	
1-2. 轴承 Bearing Type	Two Ball Bearing	
1-3. 额定电压 Rated Voltage	DC24V	
1-4. 操作电压 Operating Voltage	DC 15V~27V	
1-5. 启动电压 Start-up Voltage	<15V	25℃ Power ON/OFF
1-6 额定电流 Rated Current	1.0(Max:1.20)A	A.At Rated Voltage B.25℃ C.65%RH D.Measured after 5minutes
1-7. 额定功率 Rated Power	24.0(Max:28.8)W	
1-8. 额定转速 Rated Speed	4500rpm±10%	
1-9. 最大风量 Max. Air Flow	229.52(Min:206.57)CFM	A.PQ Measurement Apparatus B.Standard: AMCA C.Rated Voltage D.Rated Current
	6.49(Min:5.84)m³/min	
1-10. 最大静压 Max.Static Pressure	25.93(Min:21.00)mm-H ₂ O	
	1.02(Min:0.83)inch-H ₂ O	
1-11. 噪音 Noise level	64.6(Max:71.06)dBA	A.Rated Voltage B.Mute Room C.Distance:1M D.Background Noise: <18dB
1-12. 寿命预估 Life Expectance	70000hrs at 40℃ 相对湿度 15%~65%RH	L10 Failure Criteria: A.Speed:Under15% of original value B.Current:Over15% of original value C. Fan not run
1-13. 马达极数 Pole	4 Poles	
1-14. 旋转方向 Rating Direction	Anticlockwise	From the blades side/从扇叶面
1-15.其他特点Other Features	Tachometer Output 测速计输出	○
	Lock Rotor Alarm 锁定报警	●
	LD Rotor Alarm 寿命告警	○
	Auto start 自动重启	●
	Soft Start 软启动	●
	Speed Control Mode 速度控制模式	PWM
	Protection level 防护等级	IP54

2.Electrical Specification

项目 Item	条件 Condition
2-1.锁定扇叶保护功能 Locked Rotor Protection	○安规条件 Safety Condition
	●额定电压下风扇被锁定 1-3 秒时，自动断电，并在 2 至 6 秒内自动尝试启动，锁住扇叶 72 小时无损坏。Auto power off after locked at rated voltage for 1-3sec. And then circuit attempt to restart in 2 to 6 sec, There is no damage after 72hours locking.
2-2.极性保护 Polarity Protection	●Vcc 与 GND 反接时，不导通 Open circuit when Vcc&GND are exchanged
	○Vcc 与 GND 反接时，5 秒内不烧毁 Circuit won't be burned within 5seconds when Vcc&GND are exchanged
2-3.绝缘阻抗 Insulation Resistance	At least 10M Ω at 500 VDC between housing and both lead wires
2-4.绝缘耐压 Dielectric strength	Withstand 500 VAC 1 minute 1mA between housing and both lead wires

3.Specification of Main Material


3-1.外框材质 Frame	PBT UL94V-0
3-2.扇叶材质 Propeller	PBT UL94V-0
3-3.绝缘架 Bobbin	PBT UL94V-0
3-4.中管材质 Central pipe	Copper
3-5.导线 Lead wires	Red(+),Black(-),UL1007#22AWG Blue(PWM),White(RD),UL1007#24AWG, L=500 $\pm$ 15mm
3-6.端子 Connector	CP3504S001S-NH

	3-7 商 标 Label Marki ng	(1)型号/Model No:	RD1238B24H-RPS
		(2) 额 定 电 压 /Rated Voltage:	DC 24V
		(3) 安 规 电 流 /Rated Current:	1.30A
		标签尺寸/Label Size	Φ 40
		(4) 安 规 /Safety Approvals	CE UL
		(5) 生 产 代 码 : Production code	N0

4.Environmental Specification

项目 Item	条件 Condition
4-1.运转温度，湿度范围 Operating Temp. Humidity Range	Temperature: -10~+70 $^{\circ}$ C
	Humidity :15%~90%RH
4-2.保存温度，湿度范围 Storage Temp. Range	Temperature: -40~+85 $^{\circ}$ C
	Humidity :15%~90%RH


5. PWM 与转速曲线（PWM Vs RPM Curve）：



5-1.曲线说明 (Curves Instructions)：

0% RPM=0, 6% RPM=500, 94%-100% RPM=4500

5-2.PWM控制信号 (PWM CONTROLR SIGNAL)：



5-3.Input PWM频率范围：1Khz-30Khz（The Input PWM frequency range: 1Khz-30Khz）

6. RD (Rotation Detection) 运转状态监测，堵转报警：


RD：运转时信号引脚输出低电平，转子堵转时输出高电平，外部设备通过监测高低电平来分辨风扇是否处于运转还是停转。

RD:When running, output low level;when locked, output high level; External equipment will distinguish the fan is working or not through the inspection of high and low level.

6-1.RD 输出电路为集电极开路模式 (RD OUTPUT CIRCUIT---OPEN COLLECT MODE)

6-2.规格条件 (SPECIFICATION)：

$$VRD=14V_{max} \quad R_{ext}(\min)=VRD/I_{max} \quad I_{max}=5mA \quad V_{ce}=0.5V_{max}$$



Note:


6-2-1.RD 信号导线不能接触“+”和“-”引线

RD signal wire can not contact with the "+" and "-" lead wire

7.P-Q特性曲线测试(P-Q Characteristic curve test):

测试条件及方法 (Test conditions and methods)	
测试方法 (Testing Method)： 恒定电压测试 Constant Voltage	
大气压力 (Barometric Pressure)： 752.4 mmHg	额定电压 At Rated Voltage
相对 湿度 (Relative Humidity)： 66.825%	测试温度 (Temperature)： 25°
测试数据 (test data)： Max Ps :25.93mmAq Max Flow Rate :229.52CFM	

P-Q Curve (PQ曲线图)



8.有害物质含量声明 The criteria of content of fan’s material as below:

Seq.	Material/Substance	Standard Reference	Content Criteria
1	Pb	ROHS	<1000ppm
2	Hg	ROHS	<1000ppm
3	Cd	ROHS	<100ppm
4	Cr VI	ROHS	<1000ppm
5	PBB	ROHS	<1000ppm
6	PBDE	ROHS	<1000ppm
7	DBP	ROHS 2.0	<100ppm
8	BBP	ROHS 2.0	<1000ppm
9	DEHP	ROHS 2.0	<1000ppm
10	DIBP	ROHS 2.0	<1000ppm

本产品符合 RoHS2.0 标准。This model is RoHS 2.0 compliant.


9.Noise Test（噪音测试）

测试条件 Test Condition	测试方法 Test Method
1. 温度 Temperature: 26 °C	1. 测试位置 Test Position: 180°
2. 湿度 Humidity: 62 %RH	2. 测试距离 Test Distance: 1.0M From the fan intake
3. 额定电压 At Rated Voltage:24V DC	3. 背景噪音 Background Noise: 14.56dB(A)
4. 额定转速 At Rated Speed: 4500 RPM	4. 测试依照标准 IS03745执行 This test executes to IS03745 standard
测试设备 Test Equipment: AW6269双通道噪音频谱分析仪 AW6269 double channels noise Spectrum Analyzer	
测试结果 Test Result: 噪音: 64.6分贝; Leq: 64.6dB(A)	

9-1.噪音测试方法示意图（Schematic diagram of noise test method）：



10.尺寸图 Dimension Drawing:



11.Note:

11-1. 使用时请勿超出本规格所规定之极限，否则我们不保证此产品。

We will not guarantee the products if the application of our products are exceeded the limitation which is specified on this specification.

11-2.倘若要变更此份文件的任何规格，请务必事先提出需求。

In case of changes of the specification specified on this document.A written notice is requested in advance.

11-3.请勿触压着叶片以及电源线缠绕着风扇或用力拉扯电源线，如此轴心与电源线将会被损毁。

Please do not touch the impeller with the pressure and never bring the fan with lead wire.The bearing and lead wire may be damaged.

11-4. 本产品不保证因粉尘、水滴、小虫进入，而影响寿命与不良品产生。

No guarantee on the products against the safety problem or failure caused by powder dust, drop of water or insect.

11-5.如有任何资料及文件与此份资料不同，将以此份资料为主要参考。

If there is any data or related documentation different from this data sheet.This data sheet is the principle reference.

11-6.请勿在可燃性气体与任何有害环境中使用。

Please do not use the fan in the environment of corrosive gas or liquid or any detrimental gas.

11-7.组装风扇时，请特别注意，因共振或振动产生的噪音。

During the installation of the fan, please pay substantial attention to possible notice caused by resonance vibration and shock.

11-8.当搬运或作业中，风扇如从 60cm 的高度落下，将会对叶片的平衡产生若干影响，特别是滚珠轴承避免掉落。

It is very important to notify that avoid to drop from 60cm height when in any movement or operation,it will impact the balance of blade. Especially ball bearing structure is avoided to drop down.

11-9.锁外壳之螺丝扭力不得超 4Kgf。

The torque of the screw which locked the frame should not exceed 4 Kgf.

11-10.当风扇在运转时，请不要触摸叶片，这样非常危险，容易伤害到您的手指。

Please don't touch the blade when the fan at full speed running , be careful your fingers!