

Film, Metallized Polypropylene, Safety, KEMET, R46\_125C, 0.33 uF, 20%, 560 V, 275 V, 125C, Lead Spacing = 22.5mm



### General Information

<b>Dielectric:</b>	Metallized Polypropylene
<b>Style:</b>	Radial
<b>Supplier:</b>	KEMET
<b>Series:</b>	R46_125C
<b>Features:</b>	Pulse
<b>RoHS:</b>	Yes
<b>Lead:</b>	Wire Leads

### Specifications

<b>Capacitance:</b>	0.33 uF
<b>Capacitance Tolerance:</b>	20%
<b>Voltage DC:</b>	560 VDC
<b>Voltage AC:</b>	275 VAC
<b>Temperature Range:</b>	-40/+125C
<b>Rated Temperature:</b>	125C
<b>Dissipation Factor:</b>	0.1% 1kHz
<b>Max dVdt:</b>	200 V
<b>Safety Class:</b>	X2

### Dimensions

<b>L</b>	26.5mm +0.3mm
<b>H</b>	16mm +0.1mm
<b>T</b>	7mm +0.2mm
<b>S</b>	22.5mm +/-0.4mm
<b>H0</b>	18mm +/-0.5mm
<b>F</b>	0.8mm +/-0.05mm

### Packaging Specifications

<b>Packaging:</b>	Ammo, 360x340x59mm, Box
<b>Packaging Quantity:</b>	380