



Specifications
 Current Rating:2.0Amp
 Insulation Resistance:1000MΩMin.
 Dielectric Withstanding Voltage:500VAC
 Contact Resistance:20mΩMax.
 Operating Temperature:-40°C to +105°C
 Materials
 Contact Material:Phosphor Bronze
 Insulator Material:High Temperature Thermoplastic, UL 94V-0 Nylon 6T (Halogen Free) or the equivalent material

Recommended P.C.Board Layout
 (Tolerance:±0.05)

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	GENERAL TOLERANCE X:±5.0° X:±0.30 .X:±3.0° .X:±0.25 .XX:±2.0° .XX:±0.15 XXX:±1.0° .XXX:±0.10	PART NAME 品名 2.0mm FEMALE HEADER DUAL ROWS SMT TYPE 2XXXP W/ LOCATING PEG INSULATOR HEIGHT:4.0mm ROHS
DWG. 製圖 Betty	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C6802-XXBDXHYXR
DATE 制表日 2014/04/16	PAGE 張數 1 OF 1	REV. 版次 A	