

## Type **EI 38/13,5** Output Power **3,2VA**

El-Kom Code	Secondary [V]	Current [A]	No-Load [Output]	Pin Pr/Sec
RN138321	6	0,533	8,10	1-5/7-9
RN138322	7,5	0,427	10,13	1-5/7-9
RN138323	9	0,356	12,15	1-5/7-9
RN138324	12	0,267	16,20	1-5/7-9
RN138325	15	0,213	20,25	1-5/7-9
RN138326	18	0,178	24,30	1-5/7-9
RN138327	24	0,133	32,40	1-5/7-9
RN138328	30	0,107	40,50	1-5/7-9
RN138341	2 x 6	2 x 0,267	2 x 8,10	1-5/6-7,9-10
RN138342	2 x 7,5	2 x 0,213	2 x 10,13	1-5/6-7,9-10
RN138343	2 x 9	2 x 0,178	2 x 12,15	1-5/6-7,9-10
RN138344	2 x 12	2 x 0,133	2 x 16,20	1-5/6-7,9-10
RN138345	2 x 15	2 x 0,107	2 x 20,25	1-5/6-7,9-10
RN138346	2 x 18	2 x 0,089	2 x 24,30	1-5/6-7,9-10
RN138347	2 x 24	2 x 0,067	2 x 32,40	1-5/6-7,9-10



### Specifications

Potted under vacuum | Split-Bobbin Winding  
**Design** : acc. to VDE 0570, EN 61558  
**Safety Class** : II  
**Protection Index** : IP 00  
**Ambient Temp.** : ta=40°C  
**Test Voltage** : 4000V/50Hz  
 (between input & output)

**Primary** : 230 V

### Dimensions (mm) Pin: Ø 0,8

