

Aluminum Electrolytic Capacitor Specification

Series	KLH	200 V 33 μ F	Part No.	KLH-200V330KH200-T/A5.0
Customer No.	/		Case size	Φ D 12.5 X L 20
Specification	Items		Standard	
	Operating temperature range		- 25 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 10% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.15 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 198 μ A (20 $^{\circ}$ C 200 V 2 min)	
	Impedance (MAX)		1.05 Ω (100KHZ, 20 $^{\circ}$ C)	
	Ripple current (MAX)		440mA _{rms} (100KHz , 105 $^{\circ}$ C)	
	Load life		5000 hrs	
Outline	Sleeve color		Deep Green	
	Marking color		White	
	(Dimensions)			
	<p style="text-align: center;">Copper clad steel wire(tinned)</p> <p style="text-align: right;">[Remarks: Taping space: 5.0(+0.8-0.2)]</p> <p style="text-align: right;">(unit): mm</p>			
Recorder	(The first edition) : 2016-10-31			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG