

Aluminum Electrolytic Capacitor Specification

Series	KRM	400 V 10 μ F	Part No.	KRM-400V100MG160-T/A5.0
Customer No.	/		Case size	Φ D 10 X L 16
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 105 °C	
	Capacitance tolerance		\pm 20% (20°C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.15 (20°C , 120Hz)	
	Leakage current (MAX)		(Less than) 120 μ A (20°C 400 V 1 min)	
	Impedance (MAX)		/	
	Ripple current (MAX)		105 mArms (120Hz , 105°C)	
	Load life		2000hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p>The drawing shows a side view of the capacitor with the following labels and dimensions: <ul style="list-style-type: none"> Vent: A small hole on the top surface. Markings: A rectangular area on the top surface. Sleeve: A cylindrical component on the side. Copper clad steel wire(tinned): Two leads extending from the side. Dimensions: <ul style="list-style-type: none"> Height: 10+0.5 MAX Length: 16 + 1.5max Lead length: 15min Lead diameter: Φ0.6\pm0.05 Lead spacing: 4min Top View: Shows a circular cross-section with two leads and a Flat Rubber seal. The lead space is 5.0\pm0.5. Remarks: Taping space: 5.0 (+0.8-0.2) Unit: (unit):mm </p>			
Recorder	(The first edition) : 2017-4-24			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG