



Encapsulated Transformers

Type **EI 30/15,5** Output Power **2,3 VA**

| El-Kom Code | Secondary [V] | Current [A] | No-Load [Output] | Pin Pr/Sec |
|-------------|---------------|-------------|------------------|--------------|
| RN130721 | 6 | 0,383 | 9,30 | 1-5/7-9 |
| RN130722 | 7,5 | 0,307 | 11,63 | 1-5/7-9 |
| RN130723 | 9 | 0,256 | 13,95 | 1-5/7-9 |
| RN130724 | 12 | 0,192 | 18,60 | 1-5/7-9 |
| RN130725 | 15 | 0,153 | 23,25 | 1-5/7-9 |
| RN130726 | 18 | 0,128 | 27,90 | 1-5/7-9 |
| RN130727 | 24 | 0,096 | 37,20 | 1-5/7-9 |
| RN130728 | 30 | 0,077 | 46,50 | 1-5/7-9 |
| RN130741 | 2 x 6 | 2 x 0,192 | 2 x 9,30 | 1-5/6-7,9-10 |
| RN130742 | 2 x 7,5 | 2 x 0,153 | 2 x 11,63 | 1-5/6-7,9-10 |
| RN130743 | 2 x 9 | 2 x 0,128 | 2 x 13,95 | 1-5/6-7,9-10 |
| RN130744 | 2 x 12 | 2 x 0,096 | 2 x 18,60 | 1-5/6-7,9-10 |
| RN130745 | 2 x 15 | 2 x 0,077 | 2 x 23,25 | 1-5/6-7,9-10 |
| RN130746 | 2 x 18 | 2 x 0,064 | 2 x 27,90 | 1-5/6-7,9-10 |
| RN130747 | 2 x 24 | 2 x 0,048 | 2 x 37,20 | 1-5/6-7,9-10 |



Specifications

Potted under vacuum | Split-Bobbin Winding
Design : acc. to VDE 0570, EN 61558
Safety Class : II
Protection Index : IP 00
Ambient Temp. : ta=60°C
Test Voltage : 4000V/50Hz
 (between input & output)
Short Circuit Strength: Sort-Circuit-Proof
Primary : 230 V

Dimensions (mm)

Pin: Ø 0,8

