

Aluminum Electrolytic Capacitor Specification				
Series	KRM	63 V 33 μ F	Part No.	KRM-063V330ME110-T/A5.0
Customer No.	/		Case size	Φ D 6.3 X L 11
Specification	Items		Standard	
	Operating temperature range		- 55 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.09 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 20.79 μ A (20 $^{\circ}$ C 63 V 1 min)	
	Impedance (MAX)		/	
	Ripple current (MAX)		100 mArms (120Hz , 105 $^{\circ}$ C)	
	Load life		2000hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p>The drawing shows a side view of the capacitor with a vent, sleeve, and markings. Dimensions include a height of 6.3 ± 0.5 MAX, a length of 11 + 1.5max, a lead length of 15min, and a terminal width of 4min. The sleeve diameter is Φ0.5 ± 0.05. The end view shows a circular capacitor with a lead space of 2.5 ± 0.5 and a flat rubber seal. A note specifies a tapping space of 5.0 (+0.8-0.2).</p> <p>Labels in the drawing include: Vent, Sleeve, Markings, Copper clad steel wire(tinned), Flat Rubber, Lead space, and Remarks: Taping space: 5.0 (+0.8-0.2). The unit is mm.</p>			
Recorder	(The first edition) : 2017-4-24			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG