



RECOMMENDED P.C.B LAYOUT

F: 19.40 mm C: 6.00 mm D: 3.00 mm E: 10.40 mm

MATERIAL

HOUSING : THERMOPLASTIC UL94V-0
CONTACT : COPPER ALLOYS

SPECIFICATION

CURRENT: 1A
OPERATING TEMPERATURE: -55°C TO +105°C
CONTACT RESISTANCE : 20 MILLIOHMS MAX
INSULATION RESISTANCE : 5000 MEGAOHMS MIN
DIELECTRIC STRENGTH : 1000 VAC MIN

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	BETTY	 GENERAL TOLERANCE .0=±0.38 .00=±0.25 ANG=±5°	PART NAME 品名 2.0mm PIN HEADER DUAL INSULATOR SINGLE ROW 1X1P STRAIGHT TYPE H=2.0mm (C=6.0 D=3.0 E=10.4 F=19.4mm) ROHS
DWG. 製圖	BETTY		SCALE 比例 參考
DATE 制表日	2011/03/19	UNIT 單位 M M	SIZE. 紙張尺寸 A 4
		PAGE 張數 1 OF 1	REV. 版次 A