KOSHIN

| Aluminum Electrolytic Capacitor Specification | | | | |
|--|--|--------------|---|-------------------------|
| Series | KRH | 450 V 22 μ F | Part No. | KRH-450V220MH250-T/A5.0 |
| Customer No. | | | Case size | ФD12.5 X L25 |
| Specification | Items | | Standard | |
| | Operating temperature range | | - 25 ~ + 105 °C | |
| | Capacitance tolerance | | ±20% (20℃,120Hz) | |
| | Dissipation factor (MAX) | | (Less than) 0.15 (20℃ ,120Hz) | |
| | Leakage current (MAX) | | (Less than) 297 μA (20°C 450 V 1 min) | |
| | Ripple current (MAX) | | 215 mArms (120Hz ,105℃) | |
| | Impedance (MAX) | | / | |
| | Load life | | 5000 hrs | |
| Outline | Sleeving pipe basic | | PVC | |
| | (Dimensions) | | | |
| | Copper clad steel wire(tinned) Sleeve Vent Markings Taping Space 5. 0(+0.8-0.2) (unit):mm | | | |
| Recorder | (The first edition):2011-9-3 | | | |
| Recorder (The III'st edition) :2011-9-3 | | | | |
| Wrote by: YangPeng Checked by: Dingchanghua Approved by: Shenzhihong | | | | |

(Issue No.): DJJ-2875