

产品制品规格

SPECIFICATION

顾客 CUSTOMER		口 径SIZE	30.0±0.3mm
		高 度HIGH	5.0±0.3mm
型 号 MODEL NO.	顾客型号CUSTOMER' NO		
	本公司型号MAKER' NO.	样品编号	HX120712-1
编号NO:	项目 ITEM	规格SPEC	测定条件TEST COND
1	音圈阻抗(VOICE COH. IMP)	8欧±15%	At 1.0v 800Hz
2	动 作(OPERATION)	MUST BE NORMAL	AT, PROGRAM. SOURCE 0.5w
3	异常音(SWEEP TEST)	MUST BE NORMAL	SIN WAVE 2.8 V
4	最低共振频率 RESONANT FREQ (fo)	500Hz±20%Hz	WITHOUT BAFFLE
5	输出音压 (OUTPUTS. P. L)	MEANVALUEAT94± 3dB	AT 0.1W/0.1M MEASUREMENT average of F0, 1K,2K & 3K.
6	实效频率范围 (FREQ RESPONSE)	Fo-3.5KHz	OUTPUT S.P.L. -10dB
8	额定输入功率 (RATED POWER INPUT)	0.5W	AT 1.41Vrms / 48hrs (pink noise
9	最大功率 (MAX POWER IINPUT)	1 W	AT2.0Vrms, pink noise (test 5s, stop 10s / 100 cycles)
10	失真率(DISTORTION)	5% MAX	RATED POWER INPUT 1000Hz
11	连续试验 (LOAD TEST)	AFTER TEST MEET ITEM M2&3	NOISE 0.1W 24HOURS
12	耐热试验 (HEAT TEST)	AFTER TEST MEET ITEM M2&3	50±2℃ 20/25%R. H. 5HOURS
13	耐湿试验 HUMIDITY TEST	AFTER TEST MEET ITEM M2&3	40±2℃ 90/95%R. H. 5HOURS
14	耐寒试验 COLD TEST	湿度 -25℃	16小时放置1小时后
15	磁束密度(FLUX DENSITY)	GAUSS	
16	磁铁(MAGNET)		∅ 12.5mm×1.3mm
17	音圈直径(VOICE COLL DIA)		∅ 13.6mm
18	重量WEIGHT		5.0±1g