

Aluminum Electrolytic Capacitor Specification

Series	KRJ	16 V 220 μ F	Part No.	KRJ-016V221ME070-T/A2.5
Customer No.	354875		Case size	Φ D6.3X L 7
Specification	Items		Standard	
	Operating temperature range		- 55 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.16 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 35.2 μ A (20 $^{\circ}$ C 16 V 2 min)	
	Ripple current (MAX)		126 mArms (120Hz , 105 $^{\circ}$ C)	
	Impedance (MAX)		/	
	Load life		1000 hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p>The drawing shows a side view of the capacitor with a sleeve. Labels include: Sleeve, Copper clad steel wire(tinned), Φ0.45\pm0.05, Markings, 6.3+0.5 MAX, 7+1.0max, 15min, 4min, and polarity symbols \oplus and \ominus. The top view shows a circular cross-section with a lead space of 2.5\pm0.5 and a diameter of Φ6.3. A note indicates: [Remarks: Taping space:2.5(+0.8-0.2)] (unit):mm</p>			
Recorder	(The first edition) :2016-5-18			
Wrote by: Luoli		Checked by: Dingchanghua		Approved by: Shenzhihong