

## Aluminum Electrolytic Capacitor Specification

Series	KRJ	25 V 47 $\mu$ F	Part No.	KRJ-025V470ME070-T/A2.5
Customer No.	/		Case size	$\Phi$ D 6.3 X L 7
Specification	Items		Standard	
	Operating temperature range		- 55 ~ + 105 °C	
	Capacitance tolerance		$\pm$ 20% ( 20°C , 120Hz )	
	Dissipation factor (MAX)		( Less than ) 0.14 ( 20°C , 120Hz )	
	Leakage current (MAX)		( Less than ) 11.75 $\mu$ A ( 20°C 25 V 2 min )	
	Impedance (MAX)		/	
	Ripple current (MAX)		65mArms ( 120Hz , 105°C )	
	Load life		1000hrs	
Outline	Sleeving pipe basic		PVC	
	( Dimensions )			
	<p style="text-align: center;">Copper clad steel wire(tinned)</p> <p style="text-align: center;">Sleeve</p> <p style="text-align: center;"><math>\Phi</math>0.45<math>\pm</math>0.05</p> <p style="text-align: center;">Markings</p> <p style="text-align: center;">6.3<math>\pm</math>0.5 MAX</p> <p style="text-align: center;">7 +1.0max      15min      4min</p> <p style="text-align: center;">Flat Rubber</p> <p style="text-align: center;">Lead space 2.5<math>\pm</math>0.5</p> <p style="text-align: center;">【Remarks:Taping space: 2.5 (+0.8-0.2)】</p> <p style="text-align: right;">(unit):mm</p>			
Recorder	(The first edition) : 2017-4-24			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG