

Aluminum Electrolytic Capacitor Specification

Series	KLH	25 V 2200 μ F	Part No.	KLH-025V222MI220-T/A5.0
Customer No.	/		Case size	Φ D 13 X L 22
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.16 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 550 μ A (20 $^{\circ}$ C 25 V 2 min)	
	Impedance (MAX)		0.035 Ω (100KHZ, 20 $^{\circ}$ C)	
	Ripple current (MAX)		2000 mArms (100KHz , 105 $^{\circ}$ C)	
	Load life		5000 hrs	
Outline	Sleeve color		Deep Green	
	Marking color		White	
	(Dimensions)			
	<p style="text-align: center;">Copper clad steel wire(tinned)</p> <p>The drawing shows a side view of the capacitor with a cylindrical body and a vent. Labels include 'Vent', 'Sleeve', 'Markings', and 'Copper clad steel wire(tinned)'. Dimensions are given as 13+0.5 MAX for height, 22 + 2.0 max for body length, 15min for lead length, and 4min for lead spacing. A diameter of $\Phi 0.6 \pm 0.05$ is specified for the wire. Polarity is indicated with a positive (+) sign on the top lead and a negative (-) sign on the bottom lead. A top view shows a circular capacitor with a 'Flat Rubber' seal and a 'Lead space 5.0\pm0.5' between the leads. A note states '[Remarks:Taping space:5.0(+0.8-0.2)]' and '(unit):mm'.</p>			
Recorder	(The first edition) : 2016-10-31			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG