



# DSR1A~DSR1M

## Surface Mount Standard Rectifiers

### Major Ratings and Characteristics

$I_{F(AV)}$	1.0 A
$V_{RRM}$	50 V to 1000 V
$I_{FSM}$	25 A
$I_R$	5 $\mu$ A
$V_F$	1.1 V
$T_j$ max.	150 °C




### Features

- Low profile space
- Ideal for automated placement
- Glass passivated chip junctions
- Low forward voltage drop
- Low leakage current
- High forward surge capability
- High temperature soldering:  
260°C/10 seconds at terminals
- Component in accordance to  
RoHS 2002/95/1 and WEEE 2002/96/EC

### Mechanical Date

- **Case:** JEDEC SOD-123FL molded plastic body over glass passivated chip
- **Terminals:** Solder plated, solderable per J-STD-002B and JESD22-B102D
- **Polarity:** Laser band denotes cathode end



Dimensions in millimeters and (inches)

### Maximum Ratings & Thermal Characteristics & Electrical Characteristics

( $T_A = 25\text{ °C}$  unless otherwise noted)

	Symbol	DSR1A	DSR1B	DSR1D	DSR1G	DSR1J	DSR1K	DSR1M	UNIT
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum average forward rectified current	$I_{F(AV)}$	1							A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	$I_{FSM}$	25							A
Maximum instantaneous forward voltage at 1.0A	$V_F$	1.1							V
Maximum DC reverse current $T_A = 25\text{ °C}$ at Rated DC blocking voltage $T_A = 125\text{ °C}$	$I_R$	5.0 50							$\mu$ A
Typical junction capacitance at 4.0 V ,1MHz	$C_J$	15							p F
Operating junction and storage temperature range	$T_J, T_{STG}$	-55 to +150							°C



# DSR1A~DSR1M Surface Mount Standard Rectifiers

Characteristic Curves ( $T_A=25^\circ\text{C}$  unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Reverse Characteristics




Fig.5 Typical Junction Capacitance

