

Aluminum Electrolytic Capacitor Specification

Series	KRJ	35 V 10 μ F	Part No.	KRJ-035V100MB070-T2.5
Customer No.	/		Case size	Φ D 4 X L 7
Specification	Items		Standard	
	Operating temperature range		- 55 ~ + 105 °C	
	Capacitance tolerance		\pm 20% (20°C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.12 (20°C , 120Hz)	
	Leakage current (MAX)		(Less than) 3.5 μ A (20°C 35 V 2 min)	
	Impedance (MAX)		/	
	Ripple current (MAX)		27mA _{rms} (120Hz , 105°C)	
	Load life		1000hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p style="text-align: center;">Copper clad steel wire(tinned)</p> <p style="text-align: center;">Sleeve</p> <p style="text-align: center;">Markings</p> <p style="text-align: center;">Φ0.45\pm0.05</p> <p style="text-align: center;">4+0.5 MAX</p> <p style="text-align: center;">7 +1.0max</p> <p style="text-align: center;">15min</p> <p style="text-align: center;">4min</p> <p style="text-align: center;">Flat Rubber</p> <p style="text-align: center;">Lead space 1.5\pm0.5</p> <p style="text-align: center;">【Remarks:Taping space: 2.5 (+0.8-0.2)】</p> <p style="text-align: right;">(unit):mm</p>			
Recorder	(The first edition) : 2017-4-24			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG