

KOSHIN

Aluminum Electrolytic Capacitor Specification

Series	KRM	63 V 680 μ F	Part No.	KRM-063V681MJ250
Customer No.	/		Case size	Φ D 16 X L 25
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.09 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 428.4 μ A (20 $^{\circ}$ C 63 V 1 min)	
	Impedance (MAX)		\	
	Ripple current (MAX)		760 mArms (120Hz , 105 $^{\circ}$ C)	
	Load life		2000 hrs	
Outline	Sleeve color		Black	
	Marking color		White	
	(Dimensions)			
	<p>The drawing shows a side view of the capacitor with the following dimensions and labels: <ul style="list-style-type: none"> Side View: <ul style="list-style-type: none"> Height: 16+0.5 MAX Length: 25 +2.0 max Terminal length: 15min Terminal diameter: Φ0.8\pm0.05 Terminal thickness: 4min Labels: Sleeve, Vent, Markings, Copper clad steel wire(tinned), \oplus, \ominus Top View: <ul style="list-style-type: none"> Lead space: 7.5\pm0.5 Label: Flat Rubber </p> <p style="text-align: right;">(unit):mm</p>			
Recorder	(The first edition) : 2015-1-13			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG

(Issue No.) : DJJ-2875