



Model:	2LP953448		Overcharge Detection Voltage(V) 过充保护电压 (V)	4.3±0.05
Battery pack specification (电池组规格)	Min.Capacity 最低容量(mAh) (0.2C,25±3°C) ※Single cell capacity (单体电芯容量)	1600	Overdischarge Detection Voltage(V) 过放保护电压 (V)	2.4±0.1
	Typical Capacity 典型容量(mAh) (0.2C,25±3°C) ※Single cell capacity (单体电芯容量)	1700	Limited to Max loading current 仅用于最大的负载电流 peak value (A) constant (A) 峰值 2 (A) 持续 1 (A)	
	Nominal Voltage 标称电压(V)	7.4	Customer required Max loading current 客户要求最大的负载电流 peak value (A) constant (A) 峰值 (A) 持续 (A)	
	Internal impedance 内阻(≦) (mΩ,AC 1KHZ)	300	If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要)	
Ambient Conditions (环境温度)	Charge Temp. 充电温度(°C)	0-45	 EEMB BATTERY	
	Discharge Temp. 放电温度(°C)	-20-60		
	Humidity(湿度)	65±20%		

Battery protection
Related Value:
(相关的电池保护值)

Remark(备注):
1. No scratch, distortion, discoloration and leakage on the appearance of the cell (电池表面无划痕、变形、污点及漏液等现象).
2. RoHS compliant (严格按照ROHS要求生产).

Title	2LP953448-PCM-LD/	Drawn:	Hexin	Revise No.:	E4-2009
		Checked 1:	Jessie	Projection:	
File NO.	A10707	Checked 2:		Page:	1/1
		Approved:		Scale:	1.3 1
		Draw Date:	2014/12/22	Unit:	mm