



### SPECIFICATIONS

#### Material

Insulator : LCP, glass reinforced, rated UL 94V-0  
 Contact : Phosphor Bronze

#### Electrical

Current Rating : 1 Amp  
 Contact Resistance : 30 mΩ max.  
 Insulation Resistance : 3000 MΩ min.  
 Dielectric Withstanding Voltage : 500V AC for 1minute  
 Operating Temperature : -40°C to +105°C

OPTION:  
 N:W/O LOCATING PEG  
 Y:W/ LOCATING PEG

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 2.0mm FEMALE HEADER DUAL ROW SMT TYPE 2XXXP W/O LOCATING PEG INSULATOR HEIGHT:4.5mm MATERIAL:LCP ROHS
DATE 制表日 2017/07/19	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C6802-XXBDXAXXN
	PAGE 張數 1 OF 1	REV. 版次 A	