



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED

- MATERIAL
 CONTACT : BRASS
 SCREWS : M2 STEEL ZINC PLATED
 HOUSING : PA66, UL94V-0
- ELECTRICAL
 RATED VOLTAGE : 300V
 RATED CURRENT : 8A
 CONTACT RESISTANCE : 20mΩ
 INSULATION RESISTANCE : 5000MΩ/1000V
 WITHSTANDING VOLTAGE : AC1500V/1Min
 WIRE RANGE : 28-16AWG 1.5mm²
- MECHANICAL
 TEMP.RANGE : -40℃~+130℃
 MAX SOLDERING : +250℃, FOR 5 SEC.
 TORQUE : 0.2Nm(1.7IB.IN)
 STRUT LENGTH : 6-7mm

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	KF222-3.50/3.81	
X.	±0.20	X.	±2°	UNITS	mm			
.X	±0.15	.X	±1°	SHEET SIZE	A4	SERIES	KF222-3.50/3.81 SERIES	
.XX	±0.10	.XX	±0.5°	慈溪市凯峰电子有限公司 KAIFENG ELECTRONIC CO.,LTD				
DRAWING TYPE		COMPONENTS						
SCALE	1:1	SHEET	1 OF 1					
DRAWING NO.		KF381-XS6G						