



The Shipment Inspection Report of HuaWei Group

Customer	08064-宏通	Class	VS	Spec	1000μF/16wv	D/C			
Type Namer	AEC	Brand	CHANG	Style	SMD	Date			
Customer P/N		Size	10*10.5	LOT NO:		QYT			
Testing Environment	Temperature: 25±5℃;Relative Humidity:≤75%					Standard	GB/T 2828.1-2003		
Tests	Cap (uF)	DF (%)	LC (uA)	ESR(Ω)	Dimension (mm)				
Standard	-20~20%	20.00	160.00		Diameter	Height	Pin to Pin	Wire Diameter	Pin Length
Equipment	AT817	AT817	TH2685	AT817	Callipers				
Conditions	120Hz	120Hz	1min	100KHz					
MIN	800.00								
MAX	1200.00	20.0	160.00						
1	899.45	14.6	23.20						
2	899.19	14.6	20.10						
3	899.48	14.5	22.50						
4	898.43	14.5	26.30						
5	898.67	15.7	24.50						
6	899.43	15.5	28.50						
7	899.25	15.6	23.10						
8	898.47	15.2	20.60						
9	898.47	15.0	25.20						
10	898.79	15.7	22.30						
11	899.16	15.4	23.10						
12	907.64	14.2	20.50						
13	907.72	14.1	26.50						
14	906.66	14.0	24.20						
15	907.18	14.0	23.60						
16	907.35	14.2	25.20						
17	907.49	14.2	20.10						
18	907.63	14.1	26.30						
19	906.65	14.0	22.50						
20	907.14	14.2	21.70						
MIN	898.43	14.0	20.10	0.000					
MAX	907.72	15.7	28.50	0.000					
AVERAGE	902.71	14.7	23.50	#DIV/0!					
Verdict	OK	OK	OK	OK	OK	OK	OK	OK	OK
Inspection Items	Inspection		Sample Numbers	AC/Re	Assessment				
Appearance	Visual Inspection		500	0/1	OK				
Solderability	Welding Groove Method (245±5℃)		5	0/1	OK				
Carton Label	Visual Inspection		PKG	0/1	OK				
Packaging	Visual Inspection		PKG	0/1	OK				
Noted				Final Assessment	OK				
<i>Prepare :</i>				<i>Check : 陈婷</i>	<i>Approval: 朱丹</i>				