



The technical requirements:  
 1. parts shall not have flash and injection molding defects affect the use of,  
 2. the product surface is clean, smooth, no deposition mark,  
 3. "\*" is the important characteristic, "!" "As the key characteristics.  
 4. dimensions without tolerance indication according to the GB-T14486-2008-MT6 level.  
 5. Pull rod assembly direction according to customer requirements.

MARK	ECN	DESCRIPTION	DWN.	DATE

⑥	HOLDER	PA66+GF30%	1	PURPLE BOLDER	COLOUR	SEE TABLE	乐清市奥海电气有限公司				
⑤	WIRE SEAL	SILICONE RUBBER	1	RED	MATERIAL	SEE TABLE	Yueqing Aohai Electric Co., Ltd.				
④	WIRE SEAL	SILICONE RUBBER	1	RED	NAME	24HOLE CONNECTOR	DRAWN BY	CONFIRMED BY	APPROVED BY		
③	LOCK	PBT+GF15%	1	BLACK	PART NO.		HE 2013.5.4 LONG			LUO 2013.5.4 SHUPANG	
②	LOCK	PBT+GF15%	1	YELLOW	TYPE	DJ7241-1.5/2.8-21					
①	HOUSING	PBT+GF15%	1	GRAY	DRW NO. :		REV.	1st-PERSON VIEW	FREE	UNIT	PAGE
No.	PART NO.	NAME	MATERIAL	Q' TY	COLOUR	MOULD NO. :	A0	1:1	mm	1/1	

NO. TOLERANCES GB/T14486-2008-MT6			
DIM. RANGE	DIM. TOLERANCES	DIM. RANGE	DIM. TOLERANCES
0~3	±0.23	>18~24	±0.41
>3~6	±0.26	>24~30	±0.45
>6~10	±0.29	>30~40	±0.50
>10~14	±0.33	>40~50	±0.57
>14~18	±0.37	>50~65	±0.65