


## M8 Female Panel Mount, PCB Type, Front fastened

- Connector series: M8
- Gender: Female
- Coding: A,B
- Locking type: Fix screw
- Mounting type: Front fastened
- Part No.: MB08FB\*FF\*\*ST

\* refers to coding type  
 \*\* refers to pins number



### General information

Standard:	IEC 61076-2-104
Ambient temperature:	-25°C ~ +90 °C
Connector insert:	TPU
Connector contacts:	Brass with gold plated
Connector nut/screw:	Brass with nickel plated
Seal / O-ring:	Epoxy resin / FKM

Insulation resistance:	≥ 100MΩ
Contact resistance:	≤ 5mΩ
Shielding:	Unavailable
IP rating:	IP67 in locked condition
Panel cut-out:	Refer to page 73
PCB layout:	Refer to page 72

### Electrical data & Mechanical data

Contacts		Contacts termination	Rated current	Voltage	
				A/C	D/C
03 pins	(A-coding)	PCB version	3A	60V	60V
04 pins	(A-coding)	PCB version	3A	30V	30V
05 pins	(B-coding)	PCB version	3A	30V	30V
06 pins	(A-coding)	PCB version	1A	30V	30V
08 pins	(A-coding)	PCB version	1A	30V	30V

### Remarks

- Please refer to Page 14 for products' part number encoding rule.