FINECABLES ENTERPRISE CO., LIMITED



M5 Male Molded Cable, Straight


• Connector series: M5

Gender: MaleCoding: A

Locking type: Fix screwMounting type: Straight

• Part No.: MA05MAF**STXXXX14

** refers to pins number
X refers to cable specification





■ General information

Standard:	IEC 61076-2-105
Ambient temperature:	–20°C ~ +80°C
Connector insert:	TPU
Connector contacts:	Brass with gold plated
Connector overmold:	TPU
Connector nut/screw:	Brass with nickel plated

Insulation resistance:	≥ 100MΩ			
Contact resistance:	$\leq 5 \text{m}\Omega$			
Shielding:	Unavailable			
IP rating:	IP 67 in locked condition			

■ Electrical data & Mechanical data

Contacts	Rated current	Voltage		Wire gauge / size		Cable jacket	Wire	Cable ending &	
Comacis		A/C	D/C	AWG	mm²	Cable Jacket	insulation	length	
03 pins	● 1 3 ● 4	1A	60V	60V	26AWG	0.14	PUR/PVC	PVC	Customized cable
04 pins	2 • •1	1A	60V	60V	26AWG	0.14	PUR/PVC	PVC	ending and length

■ Remarks

- Please refer to Page 10 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm².
- Please refer to Page 13 for products' part number encoding rule.