



DG66-DA/DB



APPROVAL		
Electrical		
Standard	UL	IEC
Rated voltage	600V	750V
Rated current	30A	32A
Wire range	22-10AWG	4mm ²
Withstand Voltage	AC2000V/Min	
Insulation Resistance	500MΩ/DC500V	
Mechanical		
Max.Torque Value	1.2N.m 10.6Lb.in	
Ambient temperature	-40°C~+105°C	
Dimensions		
Pitch	11.11mm(.437")	
Poles	2P-12P	
Material		
Housing	PA66 UL 94V-0	
Terminal	Brass,0.8t,Tin-Plated	
Screws	Steel,M4 Ni-Plated	

Poles	2	3	4	5	6	7	8	9	10
L(mm)	23.51	34.62	45.73	56.84	67.95	79.06	90.17	101.28	112.39
S(mm)	11.11	22.22	33.33	44.44	55.55	66.66	77.77	88.88	99.99
Poles	11	12	13	14	15	16	17	18	19
L(mm)	123.50	134.61	145.72	156.83	167.94	179.05	190.16	201.27	212.38
S(mm)	111.10	122.21	133.32	144.43	155.54	166.65	177.76	188.87	199.98
Poles	20	21	22	23	24	25	26	27	28
L(mm)	223.49	234.60	245.71	256.82	267.93	279.04	290.15		
S(mm)	211.09	222.20	233.31	244.42	255.53	266.64	277.75		