




PJU70N06 / PJD70N06 / PJP70N06 / PJF70N06

60V N-Channel Enhancement Mode MOSFET

Voltage **60 V** **Current** **70 A**

Features

- $R_{DS(ON)}$, $V_{GS} @ 10V, I_D @ 20A < 8.5m\Omega$
- High switching speed
- Improved dv/dt capability
- Low reverse transfer capacitance
- Lead free in compliance with EU RoHS 2011/65/EU directive.
- Green molding compound as per IEC61249 Std.
(Halogen Free)



Mechanical Data

- Case : TO-251AA, TO-252AA, TO-220AB, ITO-220AB-F Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- TO-251AA Approx. Weight : 0.0104 ounces, 0.297grams
- TO-251AA Approx. Weight : 0.0104 ounces, 0.297grams
- TO-220AB Approx. Weight : 0.067 ounces, 1.9 grams
- ITO-220AB-F Approx. Weight : 0.068 ounces, 2 grams

Maximum Ratings and Thermal Characteristics ($T_A=25^\circ C$ unless otherwise noted)

PARAMETER	SYMBOL	TO-251AA	TO-220AB	ITO-220AB-F	TO-252AA	UNITS
Drain-Source Voltage	V_{DS}		60			V
Gate-Source Voltage	V_{GS}		<u>+25</u>			V
Continuous Drain Current Continuous Drain Current	$T_C=25^\circ C$	I_D	70			A
	$T_C=100^\circ C$		44			
Pulsed Drain Current (Note 1)	$T_C=25^\circ C$	I_{DM}		280		
Power Dissipation	$T_C=25^\circ C$	P_D	83	100	36	83
	$T_C=100^\circ C$		33	40	14	33
Continuous Drain Current	$T_A=25^\circ C$	I_D		9.9		A
	$T_A=70^\circ C$			7.9		
Power Dissipation	$T_A=25^\circ C$	P_D	2.5	2.0	1.0	2.5
Power Dissipation	$T_A=70^\circ C$		1.6	1.3	0.7	1.6
Single Pulse Avalanche Energy (Note 6)	E_{AS}			101		mJ
Operating Junction and Storage Temperature Range	T_J, T_{STG}			-55~150		°C
Typical Thermal resistance - Junction to Case - Junction to Ambient	$R_{\theta JC}$	1.5	1.25	3.5	1.5	°C/W
	$R_{\theta JA}$	50	62.5	120	50	
● Limited only By Maximum Junction Temperature						



PJU70N06 / PJD70N06 / PJP70N06 / PJF70N06

Electrical Characteristics ($T_A=25^\circ C$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=250\mu A$	60	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2	3	4	V
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=20A$	-	7	8.5	$m\Omega$
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=48V, V_{GS}=0V$	-	-	1.0	μA
Gate-Source Leakage Current	I_{GSS}	$V_{GS}=\pm 25V, V_{DS}=0V$	-	-	± 100	nA
Dynamic <small>(Note 7)</small>						
Total Gate Charge	Q_g	$V_{DS}=30V, I_D=20A,$ $V_{GS}=10V$ <small>(Note 2,3)</small>	-	50	-	nC
Gate-Source Charge	Q_{gs}		-	18	-	
Gate-Drain Charge	Q_{gd}		-	26	-	
Input Capacitance	C_{iss}	$V_{DS}=30V, V_{GS}=0V,$ $f=1.0MHz$	-	1823	-	pF
Output Capacitance	C_{oss}		-	277	-	
Reverse Transfer Capacitance	C_{rss}		-	139	-	
Turn-On Delay Time	$t_{d(on)}$	$V_{DS}=30V, I_D=20A,$ $V_{GS}=10V, R_G=25\Omega$ <small>(Note 2,3)</small>	-	20	-	ns
Turn-On Rise Time	t_r		-	24	-	
Turn-Off Delay Time	$t_{d(off)}$		-	35	-	
Turn-Off Fall Time	t_f		-	18	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I_S	---	-	-	70	A
Diode Forward Voltage	V_{SD}	$I_S=1A, V_{GS}=0V$	-	0.8	1.3	V


NOTES :

1. Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$
2. Essentially independent of operating temperature typical characteristics.
3. Repetitive rating, pulse width limited by junction temperature $T_J(MAX)=150^\circ C$. Ratings are based on low frequency and duty cycles to keep initial $T_J=25^\circ C$.
4. The maximum current rating is package limited.
5. R_{QJA} is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch 2 with 2oz.square pad of copper.
6. The test condition is $L=0.1mH, I_{AS}=45A, V_{DD}=25V, V_{GS}=10V, R_G=25ohm$, Starting $T_J=25^\circ C$
7. Guaranteed by design, not subject to production testing.



PJU70N06 / PJD70N06 / PJP70N06 / PJF70N06

Packaging Information






PJU70N06 / PJD70N06 / PJP70N06 / PJF70N06

PART NO PACKING CODE VERSION

Part No Packing Code	Package Type	Packing type	Marking	Version
PJD70N06_L2_00001	TO-252AA	3,000pcs / 13" reel	D70N06	Halogen free
PJU70N06_T0_00001	TO-251AA	80pcs / Tube	U70N06	Halogen free
PJP70N06_T0_00001	TO-220AB	50pcs / Tube	P70N06	Halogen free
PJF70N06_T0_00001	ITO-220AB-F	50pcs / Tube	F70N06	Halogen free

MOUNTING PAD LAYOUT



**PJU70N06 / PJD70N06 / PJP70N06 / PJF70N06****Disclaimer**

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.