



Ref. No. 430282 | Cat. No. FDE36TC125GF

Description: FDE 160 Breaker Icu 25 kA/415VAC Ue 690VAC 3P 3trips - 125A LTM

EAN 5050096302828

Products > Industrial Circuit Breakers > Moulded Case Circuit Breakers

Rated at 160A, the FD160 frame size is designed for use in both a DIN-rail environment with modular equipment and in industrial applications. It is supplied with IPXXB terminals suitable for direct connection of one or two conductors totalling up to 95 mm² and is available as a thermal-magnetic breaker (LT,ST). The FD160 bridges the gap between residential miniature circuit breakers and industrial moulded case circuit breakers.

Descriptors

Category	Moulded Case Circuit Breakers
----------	-------------------------------

Specifications

Series	Circuit breaker (complete breaker)
In (A)	125 A
Number of poles	3P
Trips	3 trips
Frame type	D frame (63A/160A)
Rating frame (A)	160 A
Short-circuit capacity (kA)	Effective 25 kA
Trip Unit	Line protection (thermal) (NO RCD)
Measurements	130x81x85 mm
Ui (V)	750 V
Ir (A)	125 A
IEC 230VAC	40 kA
IEC 400VAC	25 kA
IEC 440VAC	14 kA
IEC 500VAC	12 kA
IEC 690VAC	4.5 kA
IEC 690VAC Icu	4.5 kA
Im (A)	1.250 A
Standard packing	1

Classifications

ETIM 5.0	EC000228
ETIM 6.0	EC000228

Dimensions

Weight	1.050 kg
--------	----------

Publications

Title	Publication No.	Publication Type
Record Plus - FD160 Breaker/Disconnecter 3P (stp) 3D Drawing: Industrial Circuit Breaker - Record Plus - FD160 Breaker/Disconnecter 3P (STEP format)	3D-00894	Drawings - CAD - 3D
Record Plus - FD160 Breaker/Disconnecter 3P (pdf) 3D PDF Viewer: Industrial Circuit Breaker - Record Plus - FD160 Breaker/Disconnecter 3P (3DPDF format)	3D-00894-PDF	Drawings - CAD - 3D

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...