



The technical requirements:
 1 pieces of the surface are not allowed to have obvious scratches, cracks, deformation
 Stamping defects, chamfer is clear, stamping Feng is less than 0.02mm
 2 not note round R R0.2 to R0.5mm
 3 product beading and stit frener depth 0.08-0.1mm
 4 "◆" is the important characteristic; "★" as the key characteristics.
 5 did not note the size tolerance in table
 GB/T15055-2007-m.

SURFACE TREATMENT	TIN-PLATED
MATERIAL	BRASS TO.3
NAME	TERMINAL
PART NO.	SEE TABLE
DRAWN BY: AHT	CONFIRMED BY: APPROVED BY
乐清市奥海电气有限公司 Yueqing Aohai Electric Co., Ltd.	

NO. TOLERANCES GB/T15055-2007-m		NO. TOLERANCES GB/T15055-2007-m		NO. TOLERANCES GB/T15055-2007-m		NO. TOLERANCES GB/T15055-2007-m		NO. TOLERANCES GB/T15055-2007-m	
DIM. RANGE	DIM. TOLERANCES	DIM. RANGE	DIM. TOLERANCES	DIM. RANGE	DIM. TOLERANCES	DIM. RANGE	DIM. TOLERANCES	DIM. RANGE	DIM. TOLERANCES
0.5~3	±0.20	②	DJ617-2.8×0.8A	2.7	4.1	2.2	3.4	0.5-0.85	TYPE
>3~6	±0.30	①	DJ617-2.8×0.8B	3.4	4.8	3.6	4.9	1.0-2.0	DRW NO.:
>6~30	±0.40	NO.	PART NO.	W1	W2	H1	H2	Wire Range(mm ²)	MOULD NO.:
>30~120	±0.50	1	2	3	4	5	6	7	8

REV. 1.0	1st PERSON VIEW	FREE	UNIT	PAGE
			mm	1/1