



Ref. No. 112026 | Cat. No. CL01D310TD

Description: Screw terminal 3P, AC3 5.5kW 380-400V, 24V DC (GE)

EAN 8017018120264

Products > Power devices > Contactors > Series CL - Contactor series for General Purpose application

- Power circuit (AC): Up to 690V
- Control circuit:
Alternating current up to 690V AC
Direct current up to 440V DC
- Terminal numbering in accordance with EN50005 and EN 50012
- Fixing by clipping onto 35mm DIN rail EN50022-35 or by screws
- Degree of protection IP20
- screws protected against accidental contact in accordance with VDE 0106
- Three coil terminals
- The types CL...E are also suitable for AC controls
- Accessories:
Mounting possibilities of front/side instantaneous auxiliary contact blocks, timed auxiliary contact blocks, mechanical latch, transient suppressor block and interface modules
- Maximum number of auxiliary contacts: 4

Descriptors

Category	Series CL - Contactor series for General Purpose application
----------	--

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	DC
Control Voltage: DC	24 V
Terminal type	Screw terminal
Non-inductive loads AC1	25 A
Motors = 440V, 3-phase 50/60Hz AC3	12 A
Electrical endurance: # operations AC3	2 x 10 ⁶
Aux Contacts	1NO
Type	For contactors type CL - D
Admissible power AC3 220V, 230V	3 kW
Admissible power AC3 380V, 400V	5,5 kW
Admissible power AC3 415V, 440V	5,5 kW
Admissible power AC3 500V	7,5 kW
Package (pcs)	5

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Weight	0.490 kg
--------	----------

Publications

Title	Publication No.	Publication Type
Auxiliary contactor RL4RD (pdf)		
Auxiliary contactor RL4RD (3DPDF format)	3D-00016-PDF	Drawings - CAD - 3D
Auxiliary contactor RL4RD (stp)		
Auxiliary contactor RL4RD (STEP format)	3D-00016	Drawings - CAD - 3D

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...