



Ref. No. 435697 | Cat. No. FNUVD6

Description: FK-Undervoltage Release delayed 220/240VAC

EAN 5050096356975

Products > Industrial Circuit Breakers > Moulded Case Circuit Breakers

Releases

The undervoltage releases can be fitted easily and quickly in a specifically designed accessory compartment which is accessible by removing the breaker lid. This fully insulated compartment has several pouches one of which is reserved for an undervoltage release indicated by a symbol printed in the breaker case and on the auxiliary device itself. External wiring can be brought into the accessory compartment through - specifically designed and positioned - break out openings in the breaker lid, or can go through channels in the breaker rear.

Ones this is done the wiring can be stripped and easily connected to the box terminals on the internal accessories. These terminals are designed to connect wiring up to 2,5mm². The devices are designed to trip the breaker when its contacts are closed and the handle indicates the "ON" position. When the breaker contacts are open and the breaker handle indicates "OFF" or "TRIP" activating the releases will have no effect.

| Descriptors | |
|-------------|-------------------------------|
| Category | Moulded Case Circuit Breakers |
| | |

Specifications

| Series | Accessories |
|-------------------|-----------------------------|
| Range | Internal accessories |
| Number of poles | 3P / 4P |
| Frame type | K frame (800A/1250 A/1600A) |
| Type of Accessory | Undervoltage Releases |
| Accessory Detail | Release delayed |
| Standard packing | 1 |

Classifications

| ETIM 5.0 | EC001022 |
|----------|----------|
| ETIM 6.0 | EC001022 |

Dimensions

| Weight | 0.050 kg |
|--------|----------|