



Ref. No. 100226 | Cat. No. MC1C301ATD

Description: Screw terminal 3P, AC3 4kW, 24V DC, 1NC (GE)

EAN 8425095002265

Products > Power devices > Contactors > Series M - Compact contactor series up to 12A

- Control circuit:
Alternating current up to 600V
Direct current up to 250V
- Terminal numbering in accordance with EN 50012
- Fixing by clipping onto 35mm DIN rail (EN 50022) or by screws
- Degree of protection IP20 in accordance with EN 60529
- Printed circuit version available
- Screws and fast-on terminals protected against accidental contact in accordance with VDE 0106 T.100 and VBG4
- Facility to mount instant and timed auxiliary contact blocks and voltage suppressor block
- Conform to IEC/EN60947-1, IEC/EN60947-4-1, IEC/EN60947-5-1

Descriptors

Category	Series M - Compact contactor series up to 12A
----------	---

Specifications

Series	Three-pole contactors 6, 9 and 12 A (AC3)
Control circuit	DC
Aux Contacts	1NC
Control Voltage: DC	24 V
Motors = 440V, 3-phase 50/60Hz AC3	9 A
Package (pcs)	10
Frequency Coil voltages: alternating current	50 Hz / 60 Hz
Terminal type	Screw terminal
Admissible power AC3 220V, 230V	3 kW
Admissible power AC3 380V, 400V	4 kW
Admissible power AC3 500V	4 kW
Non-inductive loads AC1	20 A
Type of Control Voltage: DC	Standard

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Weight	0.210 kg
--------	----------

Publications

Title	Publication No.	Publication Type
4-pole - Auxiliary contactor MC1C-MCRC (pdf)		
4-pole - Auxiliary contactor MC1C-MCRC (3DPDF format)	3D-00067-PDF	Drawings - CAD - 3D
4-pole - Auxiliary contactor MC1C-MCRC (stp)		
4-pole - Auxiliary contactor MC1C-MCRC (STEP format)	3D-00067	Drawings - CAD - 3D

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...