



### SPECIFICATION FOR APPROVAL

**Customer:** \_\_\_\_\_

**Product Material No. :** \_\_\_\_\_

**Model No.** \_\_\_\_\_ **LF-GMR040YE** \_\_\_\_\_

**Version :** \_\_\_\_\_ **V3.0** \_\_\_\_\_

**Manufacturer:** \_\_\_\_\_ **Sichuan Ledfriend Technology Co., Ltd** \_\_\_\_\_

#### Customer Approval

<b>Tested by</b>	<b>Checked by</b>	<b>Approved by</b>

#### Ledfriend Approval

<b>Tested by</b>	<b>Checked by</b>	<b>Approved by</b>

#### The full model numbers required by customers

<b>Full model No.</b>		<b>Full model No.</b>	
<b>Full model No.</b>		<b>Full model No.</b>	

#### E.C. List

<b>Version</b>	<b>Description of change</b>	<b>Engineer</b>	<b>Date</b>
3.0	format change	Li Long	2015-10-26

Shenzhen Ledfriend Optoelectronics Co., Ltd.  
 4&5/F, Bldg 14A, Taihua Wutong Island, Gushu Development Zone, Xixiang Street, Bao'an District,  
 Shenzhen, China 518126  
 www.lifud.com, China service hotline: 400-096-6815 (China technical support: 13410244507)

<b>Model</b>	LF-GMR040YE	<b>Series</b>	AC220-240V typical linear metal case
--------------	-------------	---------------	--------------------------------------

## 1. Product description



Isolated LED driver, originally designed for class I LED luminaires and also suitable for the class II luminaires.

Category: AC220-240V typical metal case series.

Product properties: active PFC, high PF, high efficiency, low THD.

Application: commercial, residential and decorative lighting.

Warranty: 5 years (please refer to the warranty condition).

Certifications:



## 2. Technical data (1)

	Full model number	LF-GMR040YE 0750H(U)	LF-GMR040YE 0800H(U)	LF-GMR040YE 0900H(U)	LF-GMR040YE 0950H(U)
<b>Output</b>	Output voltage	27-40 VDC	27-40 VDC	27-40 VDC	27-40 VDC
	Output current	750mA	800mA	900mA	950mA
	Ripple current	< 400mA			
	Ripple voltage	≤4V			
	Current tolerance	±5%			
	Time to light	230Vac <0.5S			
	Temperature drift	±10%			
	Output Line regulation	±5%			
<b>Input</b>	Input Line regulation	±5%			
	Rated input voltage	220-240 Vac, (Max input voltage: 180-264Vac)			
	Frequency	47Hz-63Hz			
	Input current	0.3A Max			
	Power factor	≥0.95/230Vac			
	THD	≤18%			
	Efficiency	≥87%/230Vac			
	In-rush current (peak /duration)	I<60A/350uS@230Vac			
Typ. power input on stand-by	Pin<1W				
<b>Protective features</b>	No-load	Max. output voltage (no-load voltage) 55V			
	Short-circuit	Hiccup mode (auto-recovery)			
<b>Environment condition</b>	Working temperature	-30°C - +50°C			
	Working humidity	20-90%RH (no condensation)			
	Storage temperature/humidity	-40°C ~ +80°C (6 months under the class I environment); 10-90%RH (no condensation)			
	Atmospheric pressure	86-106KPa			
<b>Safety and norms</b>	Certifications	TUV, RCM, CE, CB			
	Hi-pot test	I/P-O/P: 3.75KVac, <5mA, 60S			
	Insulation resistance	I/P-O/P: 500VDC, >100MΩ			
	Surge level	Comply with IEC61000-4-5(L/N:2KV,L/PG:4KV,N/PG:4KV)			
	EMI	Comply with EN55015 , EN61000-3-2.			
	EMS	Comply with EN61000-4-2, 3, 4, 5, 6, 8, 11; EN61547.			
<b>Others</b>	Packing (weight)	Net weight: 170g±5%/pc; 48pcs/carton; 8.2KG±5%/carton. Carton size: 39 x 29 x 21 cm (L xWxH).			
	IP level	/			
	Warranty condition	5 years (Max. case temperature must not exceed 65°C).			
<b>Testing equipment</b>	AC power source: CHROMA6530, digital power meter: CHROMA66202, Oscilloscope: Tektronix DPO3014, DC electronic load: M9712B, LED board, constant temperature and humidity chamber, lightning surge generator: Everfine EMS61000-5B, rapid group pulse generator: Everfine EMS61000-4A, spectroanalyzer: KH3935, hi-pot tester: TH9201B, flicker-free tester (flicker-free coefficient tester) 60N-01, etc.				
<b>Test conditions</b>	The parameters above including the power factor, THD, efficiency are all tested under the ambient temperature 25°C and humidity 50%, AC input 230V and 90% output load.				
<b>Additional Remark</b>	1. In the power supply circuit, it is recommended that the customer should install an over-under-voltage protection and surge protection device to ensure the safety of using electricity. 2. The PC cover, shell, end caps used together with the LED driver inside the LED lamp must meet the UL94V-0 fire rating level or above.				

<b>Model</b>	LF-GMR040YE	<b>Series</b>	AC220-240V typical linear metal case
--------------	-------------	---------------	--------------------------------------

3. As a part of the LED lamp, the LED driver is not the only factor determining the EMC performance of the LED lamp. And the EMC performance is also related to the LED lamp's structure and the wire routing. Thus we strongly recommend the manufacturer of the finished LED lamp must re-confirm the EMC of the LED lamps.


**Technical data (2)**

	Full model number	LF-GMR040YE 1000H(U)	LF-GMR040YE 0600H(V)	LF-GMR040YE 0650H(V)	LF-GMR040YE 0700H(V)	
<b>Output</b>	Output voltage	27-40 VDC	35-55 VDC	35-55 VDC	35-55 VDC	
	Output current	1000mA	600mA	650mA	700mA	
	Ripple current	< 400mA	< 300mA			
	Ripple voltage	≤4V	≤6V			
	Current tolerance	±5%				
	Time to light	230Vac <0.5S				
	Temperature drift	±10%				
	Output Line regulation	±5%				
<b>Input</b>	Input Line regulation	±5%				
	Rated input voltage	220-240 Vac, (Max input voltage: 180-264Vac)				
	Frequency	47Hz-63Hz				
	Input current	0.3A Max				
	Power factor	≥0.95/230Vac				
	THD	≤18%				
	Efficiency	≥87%/230Vac				
	In-rush current (peak /duration)	I<60A/350uS@230Vac				
	Typ. power input on stand-by	Pin<1W				
<b>Protective features</b>	No-load	Max. output voltage (no-load voltage) 55V	Max. output voltage (no-load voltage) 70V			
	Short-circuit	Hiccup mode (auto-recovery)				
<b>Environment condition</b>	Working temperature	-30°C - +50°C				
	Working humidity	20-90%RH (no condensation)				
	Storage temperature/humidity	-40°C ~ +80°C (6 months under the class I environment); 10-90%RH (no condensation)				
	Atmospheric pressure	86-106KPa				
<b>Safety and norms</b>	Certifications	TUV, RCM, CE, CB				
	Hi-pot test	I/P-O/P: 3.75KVac, <5mA, 60S				
	Insulation resistance	I/P-O/P: 500VDC, >100MΩ				
	Surge level	Comply with IEC61000-4-5(L/N:2KV,L/PG:4KV,N/PG:4KV)				
	EMI	Comply with EN55015 , EN61000-3-2.				
	EMS	Comply with EN61000-4-2, 3, 4, 5, 6, 8, 11; EN61547.				
<b>Others</b>	Packing (weight)	Net weight: 170g±5%/pc; 48pcs/carton; 8.2KG±5%/carton. Carton size: 39 x 29 x 21 cm (L xWxH).				
	IP level	/				
	Warranty condition	5 years (Max. case temperature must not exceed 65°C).				
<b>Testing equipment</b>	AC power source: CHROMA6530, digital power meter: CHROMA66202, Oscilloscope: Tektronix DPO3014, DC electronic load: M9712B, LED board, constant temperature and humidity chamber, lightning surge generator: Everfine EMS61000-5B, rapid group pulse generator: Everfine EMS61000-4A, spectroanalyzer: KH3935, hi-pot tester: TH9201B, flicker-free tester (flicker-free coefficient tester) 60N-01, etc.					
<b>Test conditions</b>	The parameters above including the power factor, THD, efficiency are all tested under the ambient temperature 25°C and humidity 50%, AC input 230V and 90% output load.					
<b>Additional Remark</b>	1. In the power supply circuit, it is recommended that the customer should install an over-under-voltage protection and surge protection device to ensure the safety of using electricity. 2. The PC cover, shell, end caps used together with the LED driver inside the LED lamp must meet the UL94V-0 fire rating level or above. 3. As a part of the LED lamp, the LED driver is not the only factor determining the EMC performance of the LED lamp. And the EMC performance is also related to the LED lamp's structure and the wire routing. Thus we strongly recommend the manufacturer of the finished LED lamp must re-confirm the EMC of the LED lamps.					


<b>Model</b>	LF-GMR040YE	<b>Series</b>	AC220-240V typical linear metal case
--------------	-------------	---------------	--------------------------------------

### 3. Product Referenced Lifetime Curve

The curve below illustrates the driver's lifetime data when the LED driver's Max. case temperature reaches 40°C, 50°C, 60°C, 70°C and 80°C.



### 4. Dimensional Drawing (unit: mm)



### 5. Wire Connection Diagram:



<b>Model</b>	LF-GMR040YE	<b>Series</b>	AC220-240V typical linear metal case
--------------	-------------	---------------	--------------------------------------