



**Ref. No. 103578 | Cat. No. MC2A310AT5**

**Description: Screw terminal 3P, AC3 5.5kW, 220V/50-60Hz AC Bifreq. Coil, 1NO (GE)**

**EAN 8425095035782**

**Products > Power devices > Contactors > Series M - Compact contactor series up to 12A**

- Control circuit:  
Alternating current up to 600V  
Direct current up to 250V
- Terminal numbering in accordance with EN 50005
- Fixing by clipping onto 35mm DIN rail (EN 50022) or by screws
- Degree of protection IP20 in accordance with EN 60529
- Screws and fast-on terminals protected against accidental contact in accordance with VDE 0106 T.100 and VBG4
- Facility to mount instant and timed auxiliary contact blocks and voltage suppressor block
- Printed circuit version available
- Conform to IEC/EN60947-1, IEC/EN60947-4-1, IEC/EN60947-5-1

**Descriptors**

Category	Series M - Compact contactor series up to 12A
----------	---

**Specifications**

Series	Three-pole contactors 6, 9 and 12 A (AC3)
Control circuit	AC
Control Voltage: AC	220 V
Aux Contacts	1NO
Motors = 440V, 3-phase 50/60Hz AC3	12 A
Package (pcs)	20
Frequency Coil voltages: alternating current	50 Hz / 60 Hz
Terminal type	Screw terminal
Admissible power AC3 220V, 230V	3 kW
Admissible power AC3 380V, 400V	5.5 kW
Admissible power AC3 500V	5.5 kW
Non-inductive loads AC1	20 A

**Classifications**

ETIM 5.0	EC000066
ETIM 6.0	EC000066

**Dimensions**

Weight	0.170 kg
--------	----------