




SPECIFICATION FOR APPROVAL

CUSTOMER:				DATE:				
PART NO: LCB1608-300Y-N				DWG.NO: TE9800023				
CUSTOMER PART NO:				CUST.DWG.NO:				
(1) DIMENSIONS (UNIT: mm) <div style="text-align: center; margin: 10px 0;"> </div>				A	1.6 ± 0.2	m/m		
				B	0.8 ± 0.2	m/m		
				C	0.8 ± 0.2	m/m		
				D	0.3 ± 0.2	m/m		
				E		m/m		
				F		m/m		
				G		m/m		
				H		m/m		
				I		m/m		
				J		m/m		
(2) ELECTRICAL REQUIREMENTS								
Z (Ω)	30 ± 25%	TEST FREQ	100MHz/100mV					
RDC (Ω)	0.03 (MAX)	TEST FREQ						
IDC (mA)	3000 (MAX)	TEST FREQ						
TEST INSTRUMENTS HP4338A MILLIOHMMETER HP4291B RF IMPEDANCE/MATERIAL ANALYZER				APPROVED BY				
				CHECKED BY				
				DRAWN BY				

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

CUSTOMER :				DATE :					
PART NO: LCB1608-300Y-N				DWG.NO: TE9803183					
CUSTOMER PART NO :				CUST.DWG.NO :					
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)	DIMENSION (UNIT : mm)					
				FREQ	A	B	C	D	
SPEC	100MHz /100mV								
	30 ± 25%	0.03 (MAX)	3000 (MAX)	1.6 ± 0.2	0.8 ± 0.2	0.8 ± 0.2	0.3 ± 0.2		
1	29.3	0.010	OK	1.60	0.82	0.83	0.30		
2	29.9	0.011	OK	1.62	0.81	0.80	0.29		
3	29.4	0.008	OK	1.60	0.84	0.81	0.33		
4	29.7	0.009	OK	1.64	0.81	0.80	0.29		
5	27.6	0.010	OK	1.63	0.82	0.83	0.30		
6	28.4	0.009	OK	1.61	0.83	0.84	0.31		
7	29.5	0.008	OK	1.61	0.81	0.80	0.30		
8	26.9	0.011	OK	1.60	0.82	0.82	0.32		
9	28.2	0.009	OK	1.61	0.81	0.83	0.33		
10	30.0	0.009	OK	1.62	0.84	0.81	0.29		
X	28.89	0.009		1.614	0.821	0.817	0.306		
R	3.1	0.003		0.04	0.03	0.04	0.04		
						APPROVED BY			
									
						CHECKED BY			
									
						DRAWN BY			
									

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

LCB1608-300Y-N

