
KEMET Part Number: R75UI1100DQ40J

(75UI1100DQ40J)



Film, Metallized Polypropylene, Commercial Grade, KEMET, R75, 1000 pF, 5%, 2,000 V, 85C, Lead Spacing = 15mm



General Information	
Dielectric:	Metallized Polypropylene
Style:	Radial
Supplier:	KEMET
Series:	R75
Features:	Pulse
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	Yes
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C

Dimensions	
L	18mm +0.3mm
Н	10mm +0.1mm
Т	4mm +0.2mm
S	15mm +/-0.4mm
H0	18mm +/-0.5mm
F	0.8mm +/-0.05mm

Deckering Considerations		
Packaging Specifications		
Ammo, 360x340x59mm, Box		
1000		

Specifications	
Capacitance:	1000 pF
Capacitance Tolerance:	5%
Voltage DC:	2000 VDC
Voltage AC:	700 VAC
Temperature Range:	-55/+105C
Rated Temperature:	85C
Dissipation Factor:	0.04% 1kHz, 0.06% 10kHz, 0.25% 100kHz
Max dVdt:	9,500 V
Inductance:	10 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

