



Representative Image

**Ref. No. 104614 | Cat. No. CK95BE311N**

**Description: CK95BE311N CONTACTOR 3P 160KW 220-250V/50-60HZ**

**EAN 8425095046146**

**Products > Power devices > Contactors > 3. Series CK: High efficiency contactor 150-825A AC3.**

- Control circuit:  
Alternating current up to 690V  
Direct current up to 500V
- Power circuit up to 1000V AC
- Degree of protection: IP00
- With electronic module suitable for DC and AC (50/60Hz)

### Descriptors

Category	3. Series CK: High efficiency contactor 150-825A AC3.
----------	---

### Specifications

Series	Three- and four-pole contactors
Control circuit	AC/DC
Range	Three-pole contactors from 150 to 825A (AC3)
Aux Contacts	1NO+1NC
Package (pcs)	1
Motors = 440V, 3-phase 50/60Hz AC3	309 A
Electrical endurance: # operations AC3	1.1 x 10 <sup>6</sup>
Admissible power AC3 220V, 230V	90 kW
Admissible power AC3 380V, 400V	160 kW
Admissible power AC3 415V	160 kW
Admissible power AC3 440V	185 kW
Admissible power AC3 500V	200 kW
Control Voltage: AC/DC with electronic module (at 50-60Hz)	220-250 V
Non-inductive loads AC1	450 A

### Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

### Dimensions

Weight	6.300 kg
--------	----------

## Publications

Title	Publication No.	Publication Type
<a href="#">Series CK - Contactor 3-pole CK85B-CK09B-CK95B (stp)</a>		
3D Drawing: Controls - Series CK - Contactor 3-pole CK85B-CK09B-CK95B (STEP format)	3D-00010	Drawings - CAD - 3D
<a href="#">Series CK - Contactor 3-pole CK85B-CK09B-CK95B (pdf)</a>		
3D PDF Viewer: Controls - Series CK - Contactor 3-pole CK85B-CK09B-CK95B (3DPDF format)	3D-00010-PDF	Drawings - CAD - 3D

**Additional Documentation:** Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...