

Aluminum Electrolytic Capacitor Specification				
Series	KLH	450 V 68 μ F	Part No.	KLH-450V680MK250
Customer No.	/		Case size	Φ D18 X L 25
Specification	Items		Standard	
	Operating temperature range		- 25 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.15 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 918 μ A (20 $^{\circ}$ C 450 V 2 min)	
	Impedance (MAX)		1.8 Ω (100kHz , 20 $^{\circ}$ C)	
	Ripple current (MAX)		875mA _{rms} (100kHz , 105 $^{\circ}$ C)	
	Load life		5000hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p style="text-align: center;">Copper clad steel wire(tinned)</p> <p style="text-align: center;">Sleeve Φ0.8\pm0.05</p> <p style="text-align: center;">Vent</p> <p style="text-align: center;">Markings</p> <p style="text-align: center;">Flat Rubber</p> <p style="text-align: center;">Lead space 7.5\pm0.5</p> <p style="text-align: center;">18+0.5 MAX</p> <p style="text-align: center;">25 +2.0max 15min 4min</p> <p style="text-align: right;">(unit):mm</p>			
Recorder	(The first edition) : 2017-7-1			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG